



RECOMMENDED P.C.B LAYOUT

RoHS Compliant

Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze or Brass

Electrical

Current Rating : 1 Amp

Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.

Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	NOV.09'04
B		ADD. RoHS	DEC. 27'05

POSITION	A	B
6	12.96	5.08
8	15.50	7.62
10	18.04	10.16
12	20.58	12.70
14	23.12	15.24
16	25.66	17.78
20	30.74	22.86
24	35.82	27.94
26	38.36	30.48
28	40.90	33.02
30	43.44	35.56
34	48.52	40.64
40	56.14	48.26
50	68.84	60.96
60	81.54	73.66
64	86.62	78.74

TOLERANCE UNLESS OTHERWISE SPECIFIED	
LINEAR	ANGLE
X. ±	X° ±
.X ± 0.25	.X° ±
.XX ± 0.15	.XX° ±
.XXX±	.XXX° ±
APPD	
CHKD	
DRAW	Z DEC.27'2005



UNITS

MM

SCALE

SIZE

A4



GOLD-TEK ELECTRIC CO., LTD.

TITLE
DIP PLUG
2.54x2.54mm
CPART NO.

PART NO.
DP**TN11/RH

CAD NO. I163
F:\PDF\PH\PH-0214
SHEET
1 OF 1

圖面編號:GTKSD1331-B(1)