

SPECIFICATION

ADPV63 series AC/DC Adapter

HGPOWER

ADD: Banshang,Lijia Town, Changzhou, Jiangsu, China

TEL:86-519-86732495,86735139

WWW.hgpower.com

Post code : 213165

FAX:86-519-86731270

E-mail:lglxdh@public.cz.js.cn

RECORD OF ALTERATION

PRODUCT NAME	Switching Power for adapter
MODEL NAME	ADPV63A,B,C,E,F

REVISION:

REV NO.	01.	02.	03.	04.	05.	06.	07.	08.	09.	A	B	C	D	E
	■													

REV NO	Issue Date	Effective Date	Details of alteration content	Design	Check

TABLE OF CONTENTS

- 1. Scope**
- 2. Connecting form**

- 2.1 Input connection
- 2.2 Output cable/connection
- 2.3 Pin assignments

3. Electrical requirements

- 3.1 Input
 - 3.1.1 Input Voltage
 - 3.1.2 Input Current
 - 3.1.3 Input Frequency
 - 3.1.4 Inrush Current
 - 3.1.5 Efficiency
 - 3.1.6 Power Factor
- 3.2 Output
 - 3.2.1 Output Power
 - 3.2.2 Output Voltage
 - 3.2.3 Output Current
 - 3.2.4 Line Regulation
 - 3.2.5 Load Regulation
 - 3.2.6 Cross Regulation
 - 3.2.7 Output Ripple And Noise Voltage(Papd)
 - 3.2.8 Output Transients Response
 - 3.2.9 Output Voltage Drift
 - 3.2.10 Output Overshoot
 - 3.2.11 Output Protection
 - 3.2.11-1 Over voltage protection
 - 3.2.11-2 Output short circuit/Overload protection/TEMP protection
 - 3.2.12 output rise time
 - 3.2.13 Turn-On Delay
 - 3.2.14 Output Hold-Up- Time
 - 3.2.15 Power good/bad Signal

3.2.16 Temperature Coefficient

4. Environmental requirements

4.1 Temperature

4.2 Altitude

4.3 Humidity

4.4.1 Vibration

4.4.2 Shock/Fall

4.5 Input Transient Susceptibility

4.6 AC-Line Input Inrush Noise

5. Safety requirements

5.1 Dielectric Withstand Voltage

5.2 Leakage Current

5.3 Insulation Resistance

5.4 Safety Spacing

5.5 Safety Standards Approval

5.5.1 UL 、 C-UL Standards

5.5.2 Marking

5.6 Reliability

6. EMI Requirements

6.1 Conduction

6.2 Radiation

7. RoHS Compliant

8. Size

1. SCOPE

This is the engineering specification of ADPV63A 18Watt power wall plug-in AC/DC adapter , with wide voltage 100-240V AC input, single DC output, packed into a fully enclosed plastic case .

Models covered: ADPV63A-HGP18A12
ADPV63B-HGP16A09
ADPV63C-HGP15A06
ADPV63E-HGP12A05
ADPV63FHGP18A24

2. CONNECTOR

The following specifies the input and output connection requirement of the power supply.

2.1 INPUT CONNECTOR

Two sheet copper socket connector or two wire

2.2 OUTPUT CABLE/CONNECTOR

A two wire cable with standard right angle barrel connector, The length of the output cable is about 1.8M for all models. I attach the picture about the output plug, please check it

2.3 PIN ASSIGNMENTS

INPUT: Pin1~Line(L)

Pin1~Neutral(N)

OUTPUT: Outside ~GND

Inside~+Vout

3. ELECTRICAL REQUIREMENTS

(Unless specified otherwise, all specifications are at nominal input voltage, full load, 25 °C , PSU at warmed up condition.)

3.1 INPUT

The operating conditions with respect to the AC input voltage are described in this section.

3.1.1 INPUT VOLTAGE

The operating voltage range is 100V to 240VAC.

3.1.2 INPUT CURRENT

When the input voltage is 90V at 18W, then the max input current shall be less then 0.5A .

3.1.3 INPUT FREQUENCY

Input frequency range shall be 50/60Hz.

3.1.4 INRUSH CURRENT

Maximum inrush shall be less then 30A at 240VAC.

3.1.5 EFFICIENCY

The efficiency of the power supply is 70% nominal, Measured at Full Load and nominal AC Input voltage of 240VAC ,25 °C with the PSU warmed up, at output. O/P Cable drop of 0.20V typical is removed for this calculation.

3.1.6 POWER FACTOR

Input AC voltage connects to internal diode bridge rectifier and Filter,18W output load is >0.50

3.2 OUTPUT POWER

The operating conditions for the regulated DC output are described in this section.

3.2.1 OUTPUT POWER

Depends on models, possible Max. Output power is 18W with O/P voltage of 12V,. power for a specific model ADPV63-HGPxxAyy . “xx” is Watt.

3.2.2 OUTPUT VOLTAGE

Initial point voltage is measured at Min. Load/Half Load/Max. Load, at nominal input AC voltage, The nominal output voltage of a specific model ADPV63-HGPxxAyy . “yy” is volt. This voltage change is indicative of change due to process variation and change due to load variation. The set point tolerance is measured with reference to the respective nominal Voltage and expressed as percentage of nominal output voltage.

Model	Output	Nominal voltage	Set point tolerance	User adjust
ADPV63A-HGP18A12	+V out	+12V	<4%	NA
ADPV63B-HGP16A09	+V out	+9V	<4%	NA

ADPV63C-HGP15A06	+V out	+6V	<4%	NA
ADPV63E-HGP12A05	+V out	+5V	<4%	NA
ADPV63FHGP18A24	+V out	+24V	<4%	NA

3.2.3 OUTPUT CURRENT

Model	Output	Min.Load current	Max.Load current	Limit Current
ADPV63A-HGP18A12	+Vout=12V	0A	1.50A	3.0A
ADPV63B-HGP16A09	+Vout=9V	0A	1.80A	3.5A
ADPV63C-HGP15A06	+Vout=6V	0A	2.50A	4.0A
ADPV63E-HGP12A05	+Vout=5V	0A	2.50A	4.0A
ADPV63FHGP18A24	+Vout=24V	0A	0.75A	1.5A

3.2.4 LINE REGULATION

Regulation is measured by varying the line voltage from 100~240VAC,at full load.

Model	Output	Tolerance
All	+ Vout	<4%

3.2.5 LOAD REGULATION

Measured by varying the load current from MIN Load to FULL load at nominal AC input voltage. Measured at O/P power cord end. This measures output voltage variation of a unit due to load change and is indicative of design capability. The tolerance is measured with reference to the respective nominal voltage and expressed as percentage of nominal output voltage.

Model	Output	Tolerance
All	+ Vout	<3%

3.2.6 CROSS REGULATION

Measured at 50% load on output while any other output load changed by 50%.

ALL Models

3.2.7 OUTPUT RIPPLE AND NOISE VOLTAGE(PAPD)

Measured at full load, 100Hz bandwidth, with a 0.1uF Ceramic Cap and a 47uF

Electrolytic-Cap. Connected at the measurement point. The maximum PK-PK ripple and noise is indicated below.

Model	Output	Max pk-pk
ADPV63A-HGP18A12	+Vout=12V	<120 mV
ADPV63A-HGP16A09	+Vout=9V	<120 mV
ADPV63A-HGP15A06	+Vout=6V	<120 mV
ADPV63A-HGP12A05	+Vout=5V	<120 mV
ADPV63A-HGP18A24	+Vout=24V	<250 mV

3.2.8 OUTPUT TRANSIENT RESPONSE

The load current of measured output is changed between 10% to 100% max load for all models, at 0.1A/sec slew rate, at 100/120Hz, 50% duty cycle. The recovery time and excursion is measured when the output voltage has recovered to within 1% of the load regulation band. Expressed as percentage of the nominal voltage,

The recovery time to regulation < 1ms and Max. excursion from regulation < 3% when the all models nominal output voltage.

3.2.9 OUTPUT TRANSLIENT RESPONSE

3.2.10 OUTPUT OVERSHOOT

The overshoot voltage as a percentage of nominal output voltage at initial power up of the PSU, at 18W full load condition is indicated below. Measured with ref, to the O/P regulation band.

The output overshoot < 5% when the all models nominal output voltage.

3.2.11 OUTPUT PROTECTION

The power supply load shall be protected against a fault condition described below.

3.2.11-1 OVERVOLTAGE

N/A

3.2.11-2 OUTPUT SHORT CIRCUIT / OVERLOAD PROTECTION

The PSU shall be protected against overload as per section 3.2.3. The power supply will be protected against output short circuit. Short circuit current shall be less than 0A. Under all conditions. Output voltage of less than 50% V_{out} constitutes a short. The PSU will self recover within a max. of 30 sec. After removal of the fault.

3.2.12 OUTPUT RISE TIME

The time taken by the output to rise from 10% to 90% of the final steady state value, should be as below.

The Max rise time < 10ms, when the all models nominal output voltage.

3.2.13 TURN-ON DELAY

The run-on delay time, from the time AC power is applied to the PSU till the O/P voltage is within the regulation band. Shall be less than 10 seconds at 100VAC. Cold start.

3.2.14 OUTPUT HOLD-UP- TIME

The power supply shall maintain the output within its voltage/current specification for more than 10ms. After any loss of AC input voltage. Measured at nominal input voltage of 100-240VAC and at point when output is crossing regulation band.

3.2.15 REMOTE SENSE

N/A

3.2.16 POWER FALL / POWER GOOD SIGNAL

N/A

3.2.17 TEMPERATURE COEFFICIENT

Temperature coefficient over the entire operating temperature range of 0°C to 40°C after one hour warm-up will be as follows. The temperature coefficient $2.4\text{mV}/^\circ\text{C}$ when the all models nominal output voltage.

4. ENVIRONMENTAL REQUIREMENTS

4.1 TEMPERATURE

Operating temperature range is 0°C to 40°C at the respective rated output power, with free air convection. Surface temperature shall be less than 60°C at 25°C operating temperature. Non-operating range: -25°C to 85°C.

4.2 ALTITUDE

Maximum operating altitude: 10,000 feet. Maximum Non-operating altitude: 40,000 feet.

4.3 HUMIDITY

Non-condensing relative humidity range: 5% to 95%.

4.4.1 VIBRATION

The power supply shall meet operating, non-operating and package vibration,

Vibration	frequency	acceleration	tow time	cycle
Operating	5-500Hz	0.5G	15min,xyz all 15min	2
Non-operating	5-500Hz	1G	15min,xyz all 15min	2
Package	5-500Hz	1.5G	15min,xyz all 30min	2

4.4.2 SHOCK

The power supply shall meet operating and non operating shock. On floorboards thick for 10mm wood block.

Shock	height	direction	cycles
Operating	0.3m	xyz all 3 times	6
Non-operating	1.0m	xyz all 3 times	6

4.5 INPUT TRANSLIENT SUSCEPTIBILITY

The unit shall comply with requirements of IEC 1000-4-2, IEC 1000-4-4 and IEC 1000-4-5, will withstand ESD of 8K. Contact Discharge, will withstand ESD of 12K Air Discharge, 10 strides, both +ve and -ve, as per IEC 1000-4-2.

4.6 AC-LINE INPUT INRUSH NOISE

Minimum dielectric AC-line inrush voltage noise: Between AC input L to N:

Inrush noise	Tr /Td	Voltage	Phase	time	cycles
Operating	1.2us/50us	2.0KV	0°	1min	10
			90°	1min	10
			270°	1min	10
			360°	1min	10

4.7 THERMAL SHUTDOWN

N/A

5 SAFETY REQUIREMENTS

5.1 DIELECTRIC WITHSTAND VOLTAGE

Minimum dielectric voltage: Between input to output: 3000VAC/1 minute. Leakage current shall be 5mA

maximum.

5.2 LEAKAGE CURRENT

Maximum leakage current from primary to secondary shall be 0.25mA. Minimum voltage 240VAC

5.3 INSULATION RESISTANCE

Minimum insulation resistor from primary to secondary shall be 100M Ω . Voltage DC 500V.

5.4 SAFETY SPACINGS

6.4mm minimum between primary and secondary.

5.5 SAFETY STANDARDS APPROVAL

The power supply will meet Class II, SELV of the following safety agency requirements

5.5 UL STANDARDS

- | | | |
|-------|---------------------|--|
| 5.5.1 | 1. UL1492-2 edition | The standard for audio-video products and accessories. |
| | 2. UL6500 edition | The standard for products and accessories. |

C-UL

- | | | |
|----|------------------|--|
| 1. | CSA C22.2 No.1 | Safety of radio, television and electrical equipment. |
| 2. | CSA C13.2 No.1 | Safety of radio, television and electrical equipment. |
| 3. | CSA C22.2 No.950 | Safety of information technology equipment, including electrical business equipment. |
| 4. | CSA-E65 | The standard for information technology equipment, including electrical business equipment and associated equipment. |

5.5.2 MARKING

With the following marking: UL,C-UL, CE

5.6 RELIABILITY

MTBF@ 25°C shall be 50,000 hours min.

6 EMI REQUIREMENTS

EMI STANDARD: EN55022 CLASS B, EN6100-3-2.3, FCC CLASS B

6.1 CONDUCTION

The adapter will conform to FCC PART15 Class B, VICC Class B, and CISPR Pub.13 Class B.

6.2 RADIATION

The adapter will conform to FCC PART15 Class B, VICC Class B, and CISPR Pub.13 Class B.

7. RoHS compliant

8. Size : 73x33x52mm , as following drawing .

