



DCA/ACA CURRENT ADAPTER

Model : CA-203

- * Range : DCA, ACA, 200 A, 2000 A
- * DCA Output : 1 DCmV/1 DCA.
- * ACA Output : 1 ACmV/1 ACA.
- * Size : 210 x 64 x 33 mm



DCA/ACA CURRENT ADAPTER

Model : CA-502

- * Range : DCA, ACA, 200 A, 1000 A
- * DCA Output : 1 DCmV/1 DCA.
- * ACA Output : 1 ACmV/1 ACA.
- * Size : 185 x 78 x 30 mm



Mini ACA CURRENT ADAPTER


Model : CA-201

- * 2 ranges : 20 A, 200 A
- * Output : 1 ACmV per 1 ACA (200 A) .
10 ACmV per 1 ACA (20 A) .
- * Size : 180 x 47 x 35 mm.

DCA/ACA CURRENT ADAPTER

Model : CA-501 (200A, 400A)

- * Output : 1 ACmV/1 ACA, 1 DCmV/1 DCA.
- * CA-501 : 200 x 80 x 30 mm.
- * CA-202 : 185 x 78 x 30 mm.



50A/50mV SHUNT

Model : ST-50

- * Resistance shunt match DMM DC 200 mV range to measure current up to DC/AC 50A precisely.
- * Output - 1 ACmV/1 ACA, 1 DCmV/1 DCA.
- * Size : 135 x 30 x 30 mm.



PROXIMITY SENSOR

Model : PX-01

- * DT-2240D, PDT-2250, TR-RPM1A4 sensor or position detect.
- * Detectable Object : Metals object.
- * Detecting distance : 4 mm.
- * Power : 12-24 DCV, Out-12 DCV 100 mA.

PROXIMITY SENSOR, mini & round type

Model : PX-02

- * Mini type proximity sensor.
- * Dia. 6.4 mm x 42 mm (length) .
- * PNP, normal open. Sn. : 1.5 mm.
- * Power : 10 to 55 VDC. Output : 150 mA.

PHOTO SENSOR (Photo Interrupter)

Model : PI-06

- * Photo interrupter or the photo sensor for DT-2240D, PDT-2250, TR-RPM1A4.
- * Power supply : DC 12V to 30V.
- * 3 wires : Power, Signal and Ground.

TACHOMETER ADAPTER

Model : TA-601

- * Photo type, 2 ranges, 100-20,000 RPM.
- * Output : 0.1 DC mV/1 RPM (range A),
0.1 DC mV/10 RPM (range B).
- * Size : 190 x 73 x 37 mm.



HOLSTER

Model : HS-02

- * High quality rubber protective holster.
- * Available for : EMF-822A, PH-201, CD-4302, TM-914C/F, WA-300, ORP-203 LX-100, LX-101A, LX-103.

HOLSTER

Model : HS-01

- * High quality rubber protective holster. Refer to page 32.