





ROTARY ISOLATORS

Isolators Rated Voltage: 690VAC.





12-40A









finger safe.

Rated Current	ΙΤΗ	AC21 @ 400VAC	AC23 @ 400VAC	1 Pole Code	Panel Depth	2 Pole Code	Panel Depth	3 Pole Code	Panel Depth	4 Pole Code	Panel Depth	Plate Size
12A	16A	7.5kW	4kW	AN5500000	30.5mm	AN5510000	30.5mm	AN5520000	40.5mm	AN5530000	40.5mm	
16A	20A	11kW	5.5kW	AN5501000	30.5mm	AN5511000	30.5mm	AN5521000	40.5mm	AN5531000	40.5mm	48x48mm
25A	32A	15kW	7.5kW	AN5502000	30.5mm	AN5512000	30.5mm	AN5522000	40.5mm	AN5532000	40.5mm	
32A	40A	18.5kW	11kW	AN5503100	36.3mm	AN5513100	36.3mm	AN5523100	48.3mm	AN5533100	48.3mm	60x60mm
40A	50A	22kW	18.5kW	AN5504100	36.3mm	AN5514100	36.3mm	AN5524100	48.3mm	AN5534100	48.3mm	оохоонин
63A	70A	37kW	22kW	AN5506100	46mm	AN5516100	46mm	AN5526100	62.5mm	AN5536100	62.5mm	
80A	100A	45kW	30kW	-	-	AN5518100	46mm	AN5528100	62.5mm	AN5538100	62.5mm	
100A	100A	55kW	30kW	-	-	AN5517100	46mm	AN5527100	62.5mm	AN5537100	62.5mm	
125A	125A	75kW	37kW	-	-	-	-	AN5529100	62.5mm	AN5539100	62.5mm	66x66mm
160A	160A	90kW	52kW	-	-		-	AN552A100	95.5mm	AN553A100	95.5mm	
200A	200A	110kW	65kW	-	-		-	AN552B100	95.5mm	AN553B100	95.5mm	
250A	250A	132kW	-		-		-	AN552C100	95.5mm	AN553C100	95.5mm	

Spare Handles for Isolators













Rated Current	Black Handle c/w Plate 0-1
12-25A	AR0386040
32-40A	AR0386140
63-80A	AR0386640
100-250A	AR0386840

Α		Black/Grey	Red/Yellow	Black/Grey	Red/Yellow
	White Handle c/w Plate 0-1	Padlockable	Padlockable	Padlockable (3 lock)	Padlockable (3 lock)
	AR0386010	AK1200143	AK1200523	AK1300143	AK1300523
	AR0386110	AK1200143	AK1200523	-	-
	AR0386610	AK1200146	AK1200526	-	-
	AR0386810	AK1200148	AK1200528	-	-

CHANGE OVER SWITCHES

Rated Voltage: 690VAC













0	
2	
SWIT	
O)	
60	
10	
FUSES	
ဟ	
11	
The same of	
4.5	
O)	
BREAKERS	
LLL	
⋖	
III	
$\overline{\sim}$	
0.0	
-	
SIRCUIT	
04	
0	

mount. For other mounting

12-40A

Rated Current	ITH	AC21 @ 400VAC	AC23 @ 400VAC	2 Pole Code	Panel Depth	3 Pole Code	Panel Depth	4 Pole Code	Panel Depth	Plate Size
16A	20A	11kW	5.5kW	-	-	AN5621000	50.5mm	AN5631000	60.5mm	48x48mm
25A	32A	15kW	7.5kW	-		AN5622000	50.5mm	AN5632000	60.5mm	4004011111
32A	40A	18.5kW	11kW	AN5613100	48.3mm	AN5623100	60.3mm	AN5633100	72.3mm	60x60mm
40A	50A	22kW	18.5kW	-	-	AN5624100	60.3mm	AN5634100	72.3mm	OOXOOIIIII
63A	70A	37kW	22kW	AN5616100	62.5mm	AN5626100	79mm	AN5636100	95.5mm	
80A	100A	45kW	30kW	-	-	AN5628100	79mm	AN5638100	95.5mm	
100A	100A	55kW	30kW	-	-	AN5627100	79mm	AN5637100	95.5mm	
125A	125A	75kW	37kW	-	-	AN5629100	79mm	AN5639100	95.5mm	66x66mm
160A	160A	90kW	52kW	-	-	AN562A100	128.5mm	AN563A100	161.5mm	
200A	200A	110kW	65kW	-	-	AN562B100	128.5mm	AN563B100	161.5mm	
250A	250A	132kW	_		_	AN562C100	128 5mm	AN563C100	161 5mm	

183

TEC

2023/08/23, 10:04 1 of 2



	AC21	ounting is	16A	20,		with operating hand	40A	75A	115A		
OFF	AC23	Α	12A	16		25A	32A	63A	100A		
	1 Pole		VB0728	VB0	751	VB0769	VB0777	VB079	3 -		
ON	2 Pole		VB0801	VB0	835	VB0843	VB0850	VB087	6 -		
	3 Pole		VB0884	VB0		VB0926	VB0934	VB095			
unt	4 Pole		VB1056	VB1		VB1018	VB1106	VB112	Security of		
	-	Size (mm)	48x48	48x		64x64	64x64	96x96	96x9	6	
1	Spare (Operating	Handles c/w Es	cutcheon	Plate			T			
PL-2	Black e plate s (mm)	escutcheon ize	PL-1 52 x 52	PL - 52 x	-1 52	PL-2 75 x 75	PL-2 75 x 75	VB-3 96 x 96	VB-3 96 x 96	3 96	
dle		ith yellow kable size	3L-2 Ø64	3L- Ø6		3L-2 Ø64	3L-2 Ø64	3L-3 96 x 96	3L-3		
9	Isolator	22mm Ø	Door Mount (48	3x48)							
	AC21		16A			20A	32A		40A		
	AC23		12A			16A	25A		32A		
ON	2 Pole 3 Pole		CR01600	CASC PROPERTY.		CR0200002	CR0320		CR0400002	CR0400002	
J	4 Pole		CR01600			CR0200003 CR0200004	CR0320		CR0400004		
Mount			able Front Door		San Control	JR0200004	CRU320	1004	CK040000	•	
	AC21	padioon	16A		, KOI,	20A	32A 25A CR03200G3		40A 32A CR04000G3		
	AC23		12A	12A CR01600G3		16A					
	3 Pole					CR02000G3					
e	4 Pole		CR01600		,	CR02000G4	CR0320	0G4	CR04000G	4	
		tors with ca	vitches - Door M	Vount							
100	AC-1	AC23	1 Phase * Rev	ersina	3 Ph	ase Reversing	Star-delt	a	Plate Size (mm	
ı	16A	12A	VB1940		VB1	- 10 To	VB1841	1	48 x 48		
	20A	16A			VB1	619	VB1866		48 x 48		
70	32A	25A			VB1	635	VB1882	2	64 x 64		
TAR	40A	32A			VB1	643	VB1890)	96 x 96		
LTA	50A	40A			VB1	650	VB1908	3	96 x 96		
5	Motor (Control Sv	vitches - 22mm	Door Mou	unt						
1	16A	12A	-		CR0	160008			48 x 48		
	20A	16A	-		CR0	200008			48 x 48		
ı	32A	25A	-		100000000000000000000000000000000000000	320008			48 x 48		
	40A	32A	-		CR0	400008			48 x 48		
		T-1	es Rear Door M	ount							
	400000000000000000000000000000000000000	iption	AC21A		Cod	A comment	Plate I	Marking	Size (mm)		
		step+ off	16A		VB3		0-1-2-3		48 x 48		
		step+ off	16A		VG5		0-1-2-1-		48 x 48		
		step+ off	16A		VF3		0-1-2-3-	4-5-6-7	48 x 48		
		N 100 200 200 1000 200 200 200 200 200 20	20Amps AC23		spring r			Eschutcheon F	Plate		
	2 Pole		4 Pole:			6 Poles		'ہہُ ا	1		
	R201-	23	R202-2	23		R203-23		()			

2 of 2