

PVC绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Ring Terminal (Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin




RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RV0.5-3	0.2-0.75	0.5	10A	#4	3.2	5.7	18.3	5.4	2.7	1.3	黄 yellow	
RV0.5-3.5S				#6	3.7	5.7	18.3	5.4	10.0	2.7		1.3
RV0.5-3.5M				#6	3.7	6.6	19.9	6.3				
RV0.5-4				#8	4.3	6.6	19.9	6.3				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RV1.25-3	0.5-1.5 (22-16)	0.75	19A	#4	3.2	5.7	17.8	4.9			红 red	
RV1.25-3.5S				#6	3.7	5.7	17.8	4.9				
RV1.25-3.5M				#6	3.7	6.6	20.1	6.3				
RV1.25-3.5L				#6	3.7	8.0	21.5	7.6				
RV1.25-4S				#8	4.3	6.6	20.1	6.3				
RV1.25-4L				#8	4.3	8.0	21.5	7.0				
RV1.25-5S				#10	5.3	8.0	21.5	7.0	10.7	4.2		1.7
RV1.25-5L				#10	5.3	9.8	23.0	7.6				
RV1.25-6S				1/4	6.4	9.8	23.0	7.6				
RV1.25-6L				1/4	6.4	11.6	27.5	11.1				
RV1.25-8	5/16	8.4	11.6	27.5	11.1							
RV1.25-10	3/8	10.5	13.6	31.6	13.9							
RV1.25-12	1/2	13.0	19.2	36.0	16.5							

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RV2-3	1.5-2.5 (16-14)	0.8	27A	#4	3.2	6.6	18.5	4.3			蓝 blue	
RV2-3.5S				#6	3.7	6.6	18.5	4.7				
RV2-3.5M				#6	3.7	6.6	20.0	6.0				
RV2-3.5L				#6	3.7	8.5	22.5	7.7				
RV2-4S				#8	4.3	6.6	20.0	6.5				
RV2-4L				#8	4.3	8.5	22.5	7.7				
RV2-5S				#10	5.3	8.5	22.5	7.7	10.7	4.9		2.3
RV2-5L				#10	5.3	9.5	22.5	7.0				
RV2-6S				1/4	6.4	9.5	22.5	7.0				
RV2-6L				1/4	6.4	12.0	27.6	11.0				
RV2-8	5/16	8.4	12.0	27.6	11.0							
RV2-10	3/8	10.5	14.6	31.2	13.0							
RV2-12	1/2	13.0	19.2	35.7	15.5							



PVC绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Ring Terminal (Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin




RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RV3.5-4	2.5-4 (14-12)	1.0	37A	#8	4.3	8.0	25.3	7.7			黑 black	
RV3.5-5S				#10	5.3	8.0	25.3	7.7				
RV3.5-5L				#10	5.3	12.0	27.9	9.3	13.8	5.8		3.0
RV3.5-6				1/4	6.4	12.0	29.0	9.3				
RV3.5-8				5/16	8.4	15.0	35.0	14				
RV3.5-10	3/8	10.5	15.0	34.6	14							

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RV5.5-3	4-6 (12-10)	1.0	48A	#4	3.2	7.2	22.7	6.1			黄 yellow	
RV5.5-3.5				#6	3.7	7.2	22.7	5.9				
RV5.5-4S				#8	4.3	7.2	22.7	5.9				
RV5.5-4L				#8	4.3	9.5	25.3	8.3				
RV5.5-5				#10	5.3	9.5	25.3	8.3	14.0	6.3		3.4
RV5.5-6				1/4	6.4	12.0	30.0	11.0				
RV5.5-8				5/16	8.4	15.0	34.7	13.7				
RV5.5-10				3/8	10.5	15.0	34.7	13.7				
RV5.5-12				1/2	13.0	19.2	39.0	16.0				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RV8-4	6.0-10 (8)	1.2	62A	#8	4.3	8.8	32.3	11.0			红 red	
RV8-5S				#10	5.3	8.8	32.3	13.3				
RV8-5M				#10	5.3	12.0	32.3	9.3				
RV8-5L				#10	5.3	15.0	38.3	13.8				
RV8-6S				1/4	6.4	12.0	32.3	9.8	17.0	8.0		4.5
RV8-6L				1/4	6.4	15.0	38.3	13.8				
RV8-8				5/16	8.4	15.0	38.3	13.8				
RV8-10				3/8	10.5	15.0	38.3	13.8				
RV8-12				1/2	13.0	22.0	43.0	20.5				



尼龙绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: 尼龙
- 温度: 105°C
- 表面处理: 镀锡


Nylon-Insulated Ring Terminal
(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Nylon
- Temperature: 105°C
- Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺钉口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RVN 1.25-3				#4	3.2	5.7	18.5	4.9			红 red	
RVN 1.25-3.5S				#6	3.7	5.7	18.5	4.9				
RVN 1.25-3.5M				#6	3.7	6.6	20.8	6.3				
RVN 1.25-3.5L				#6	3.7	8.0	22.2	7.6				
RVN 1.25-4S				#8	4.3	6.6	20.8	6.3				
RVN 1.25-4L				#8	4.3	8.0	22.2	7.0				
RVN 1.25-5S	0.5-1.5 (22-16)	0.75	19A	#10	5.3	8.0	22.2	7.0	11.0	4.3		1.7
RVN 1.25-5L				#10	5.3	9.8	23.7	7.6				
RVN 1.25-6S				1/4	6.4	9.8	23.7	7.6				
RVN 1.25-6L				1/4	6.4	11.6	28.2	11.1				
RVN 1.25-8				5/16	8.4	11.6	28.2	11.1				
RVN 1.25-10				3/8	10.5	13.6	32.3	13.9				
RVN 1.25-12				1/2	13.0	19.2	36.7	15.5				



尼龙绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: 尼龙
- 温度: 105°C
- 表面处理: 镀锡

Nylon-Insulated Ring Terminal
(Apply in flexible wire)


- Terminal Body: Copper
- Insulation: Nylon
- Temperature: 105°C
- Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺钉口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RVN 3.5-4				#8	4.3	8.0	25.2	7.7			黑 black	
RVN 3.5-5S				#10	5.3	8.0	25.2	7.7				
RVN 3.5-5L				#10	5.3	12.0	27.3	9.3				
RVN 3.5-6	2.5-4.0 (14-12)	1.0	37A	1/4	6.4	12.0	28.6	9.3	13.3	6.0		3.0
RVN 3.5-8				5/16	8.4	15.0	34.2	14				
RVN 3.5-10				3/8	10.5	15.0	34.2	14				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺钉口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		DΦ	dΦ
RVN 5.5-3				#4	3.2	7.2	23.0	5.9			黄 yellow	
RVN 5.5-3.5				#6	3.7	7.2	23.0	5.9				
RVN 5.5-4S				#8	4.3	7.2	23.0	5.9				
RVN 5.5-4L				#8	4.3	9.5	25.5	8.3				
RVN 5.5-5	4-6 (12-10)	1.0	48A	#10	5.3	9.5	25.5	8.3	14.0	6.6		3.4
RVN 5.5-6				1/4	6.4	12.0	30.3	11.0				
RVN 5.5-8				5/16	8.4	15.0	34.7	13.7				
RVN 5.5-10				3/8	10.5	15.0	34.7	13.7				
RVN 5.5-12				1/2	13.0	19.2	39.5	16.0				




尼龙绝缘护套圆形端子(加护套)(适用于软线)

- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105℃
 - 表面处理: 镀锡
- Nylon-Insulated Ring Terminal(Double Copper Sleeve)
(Apply in flexible wire)
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105℃
 - Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		Dφ	dφ
RVN 1.25-3 D				#4	3.2	5.7	18.5	4.9			红 red	
RVN 1.25-3.5S D				#6	3.7	5.7	18.5	4.9				
RVN 1.25-3.5M D				#6	3.7	6.6	20.8	6.3				
RVN 1.25-3.5L D				#6	3.7	8.0	22.2	7.6				
RVN 1.25-4S D				#8	4.3	6.6	20.8	6.3				
RVN 1.25-4L D				#8	4.3	8.0	22.2	7.0				
RVN 1.25-5S D	0.5-1.5 (22-16)	0.75	19A	#10	5.3	8.0	22.2	7.0	11.0	3.8		1.7
RVN 1.25-5L D				#10	5.3	9.8	23.7	7.6				
RVN 1.25-6S D				1/4	6.4	9.8	23.7	7.6				
RVN 1.25-6L D				1/4	6.4	11.6	28.2	11.1				
RVN 1.25-8 D				5/16	8.4	11.6	28.2	11.1				
RVN 1.25-10 D				3/8	10.5	13.6	32.3	13.9				
RVN 1.25-12 D				1/2	13.0	19.2	36.7	15.5				



尼龙绝缘护套圆形端子(加护套)(适用于软线)

- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105℃
 - 表面处理: 镀锡
- Nylon-Insulated Ring Terminal(Double Copper Sleeve)
(Apply in flexible wire)
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105℃
 - Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		Dφ	dφ
RVN 3.5-4 D				#8	4.3	8.0	25.2	7.7			黑 black	
RVN 3.5-5S D				#10	5.3	8.0	25.2	7.7				
RVN 3.5-5L D				#10	5.3	12.0	27.6	9.3				
RVN 3.5-6 D	2.5-4.0 (14-12)	1.0	37A	1/4	6.4	12.0	28.6	9.3	13.3	5.4		3.0
RVN 3.5-8 D				5/16	8.4	15.0	34.2	14				
RVN 3.5-10 D				3/8	10.5	15.0	34.2	14				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color		
						W	L	F	E		Dφ	dφ
RVN 5.5-3 D				#4	3.2	7.2	23.0	6.1			黄 yellow	
RVN 5.5-3.5 D				#6	3.7	7.2	23.0	5.9				
RVN 5.5-4S D				#8	4.3	7.2	23.0	5.9				
RVN 5.5-4L D				#8	4.3	9.5	25.5	8.3				
RVN 5.5-5 D	4-6 (12-10)	1.0	48A	#10	5.3	9.5	25.5	8.3	14.0	6.1		3.4
RVN 5.5-6 D				1/4	6.4	12.0	30.3	11.0				
RVN 5.5-8 D				5/16	8.4	15.0	34.7	13.7				
RVN 5.5-10 D				3/8	10.5	15.0	34.7	13.7				
RVN 5.5-12 D				1/2	13.0	19.2	39.5	16.0				