

International Components Distributor

TEL JHB: (011) 493-9307 CAPE: (021) 535-3150 KZN: (031) 309-7686

FAX: (011) 493-9319

sales@mantech.co.za

www.mantech.co.za

ZINK 62

RUST PROTECTOR

ZINK 62 is a zinc-based galvanic rust protector containing zinc with a purity over 95 %.

It prevents rust and provides long-lasting protection against aggressive environmental factors to all types of ferrous metals.

Where galvanised surfaces have become damaged or altered through drilling, cutting, welding or screwing, reliable corrosion protection, is required.



FEATURES	APPLICATIONS
Forms a resistant, flexible, electrically conductive, protective film.	 Can be used in: Gas, water and electricity supply companies Power stations Transformers Railway equipment Street-lighting Car bodywork manufacture
Good adhesion on the base metal.	
 Protects the base metal even when scratched or damaged. 	
Excellent weldability.	
Will not flake off.	 Can prevent salt water corrosion in shipping and coastal area installations.
Lead and chromate free.	

Colour :	grey
Densityat 20°C :	0,98 g/cm³
Tack-free time :	approx. 15 min.
Hardening time : (30 µm film thickness)	24 hours (20°C)
Coverage :	15 m² / I
Temperature resistance :	200°C continuous

PO BOX 260455 - EXCOM - 2023 - SOUTH AFRICA





