

LCR, Capacitance SERIES

LCR



LCR METER, professional, RS-232/USB Model : LCR-9073A

- * Intelligent microprocessor circuit, professional.
- * L : 5 ranges, 2 mH to 20 H.
- * C : 6 ranges, 2 nF to 200 μ F.
- * R : 6 ranges, 200 ohm to 20M ohm, Diode test.
- * Test frequency : 100 Hz, 1 K Hz.
- * Memory record, RS232/USB interface.
- * Size : 204 x 90 x 36 mm.

HEAVY DUTY ALLIGATORS

Model : AL-04

- * CATII 600V approval, black & red, suitable for banana plug and wire direct connection.

Model : AL-05, CATII 1000V



ALLIGATOR TEST LEAD

Model : TL-02AS

- * High quality test lead with silicon rubber wire & alligator clip sets.

SMD TEST CLIPS

Model : TL-02AS

- * The test clips used for measuring the SMD components (resistor, capacitor, inductor, diode..)
- * Cable length : approx x 90 cm.



LCR METER

Model : LCR-9083

- * Inductance, Capacitance, Resistance, Diode.
- * L : 5 ranges, 2mH to 20H.
- * C : 6 ranges, 2 nF to 200 μ F.
- * R : 6 ranges, 200 ohm to 20 M ohm.
- * Size : 185 x 87 x 39 mm, 18 mm LCD.



POCKET LCR METER

Model : LCR-9063

- * Pocket size, 13 mm LCD, Max. 1999.
- * L- 5 ranges, 2 mH to 20 H.
- * C- 6 ranges, 2 nF to 200 μ F.
- * R- 6 ranges, 200 ohm to 20 M ohm.
- * Economical type.
- * Size : 120 x 72 x 37 mm.



CAPACITANCE METER

MODEL : DM-9023

- * 9 ranges, 200pF, 2nF, 20nF, 200nF, 2 μ F, 20 μ F, 200 μ F, 2000 μ F, 20000 μ F.
- * Rotary sw., 18 mm LCD, Max. 1999.
- * Size : 185 x 87 x 39 mm.



HOLSTER

Model : HS-01

- * High quality rubber protective holster,
- * Application for : DM-9090, DM-9080, DM-9027T, DM-9030, DM-9680, LCR-9083, DM-9023.