



**ELECTRONICS, INC.**  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089

## NTE36 (NPN) & NTE37 (PNP) Silicon Complementary Transistors AF Power Amplifier, High Current Switch

**Description:**

The NTE36 (NPN) and NTE37 (PNP) are silicon complementary transistors in a TO3P type case designed for AF power amplifier and high current switching applications.

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Collector–Emitter Voltage, $V_{CEO}$ .....	140V
Collector–Base Voltage, $V_{CBO}$ .....	160V
Emitter–Base Voltage, $V_{EBO}$ .....	6V
Collector Current, $I_C$	
Continuous .....	12A
Peak .....	15A
Total Power Dissipation ( $T_C = +25^\circ\text{C}$ ), $P_D$ .....	100W
Operating Junction Temperature, $T_J$ .....	+150°C
Storage Temperature Range, $T_{stg}$ .....	–40° to +150°C

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cutoff Current	$I_{CEO}$	$V_{CB} = 80V, I_E = 0$	–	–	0.1	mA
Emitter Cutoff Current	$I_{EBO}$	$V_{BE} = 4V, I_C = 0$	–	–	0.1	mA
DC Current Gain	$h_{FE1}$	$V_{CE} = 5V, I_C = 1A$	60	–	200	
	$h_{FE2}$	$V_{CE} = 5V, I_C = 6A$	20	–	–	
Gain Bandwidth Product	$f_T$	$V_{CE} = 5V, I_C = 1A$	–	15	–	MHz
Output Capacitance	$C_{ob}$	$V_{CB} = 10V, f = 1MHz$	–	210	–	pF
NTE36			–	300	–	
Base–Emitter Voltage	$V_{BE}$	$V_{CE} = 5V, I_C = 1A$	–	–	1.5	V
Collector–Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 5A, I_B = 500mA$	–	0.6	2.5	V
NTE36			–	1.1	–	
NTE37						

**Electrical Characteristics (Cont'd):** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector–Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 5\text{mA}, I_E = 0$	160	–	–	V
Collector–Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 5\text{mA}, R_{BE} = \infty$	140	–	–	V
		$I_C = 50\text{mA}, R_{BE} = \infty$	140	–	–	V
Emitter–Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 5\text{mA}, I_C = 0$	6	–	–	V
Turn–On Time NTE36 NTE37	$t_{on}$	$10I_{B1} = -10I_{B2} = I_C = 1\text{A},$ $PW = 20\mu\text{s}$	–	0.26	–	$\mu\text{s}$
			–	0.25	–	
Fall Time NTE36 NTE37	$t_f$		–	0.68	–	$\mu\text{s}$
			–	0.53	–	
Storage Time NTE36 NTE37	$t_{on}$		–	6.88	–	$\mu\text{s}$
			–	1.61	–	

Note 1. Matched complementary pairs are available upon request (NTE37MCP). Matched complementary pairs have their gain specification ( $h_{FE}$ ) matched to within 10% of each other.

