

**SCOPE PROBE X1-X10 SWITCH 40MHZ**

- Oscilloscope probe
- BNC connectors
- Spring loaded hooks / tips

**FEATURES**

NEW AND HIGH-QUALITY MATERIALS

SMOOTH SURFACE IS COMFORTABLE IN HAND FEEL

SOLID STRUCTURE AND HIGH STRENGTH

HIGH SENSITIVITY, EXCELLENT PERFORMANCE AND RELIABLE FUNCTION

INJECTION MOLDING GROUND WIRE TO ENSURE ITS SERVICE LIFE

EASY TO OPERATE

LOW POWER CONSUMPTION

## SPECIFICATIONS

<b>TYPE</b>	P6020, P6040, P6060, P6100, P6150, P6200
<b>ATTENUATION RATIO</b>	1X/10X
<b>INPUT RESISTANCE</b>	1MΩ/10MΩ (OHM)
<b>INPUT CAPACITANCE</b>	1X: 85Pf~120pF 10X: 18.5pF~22.5pF
<b>COMPENSATION RANGE</b>	10pF~30pF
<b>SYSTEM BANDWIDTH</b>	1X: DC-6MHZ 10X: DC-20MHZ, 40MHZ, 60MHZ, 100MHZ, 150MHZ, 200MHZ
<b>INPUT VOLTAGE</b>	1X: <300VDC + AC Vp-p 10X: <600VDC + AC Vp-p
<b>WORKING TEMPERATURE</b>	-15°C ~ +75°C
<b>NO LOAD TEMPERATURE</b>	-20°C ~ +60°C
<b>FINISH</b>	INJECTION MOLDING
<b>COLOUR / COLOR</b>	GREY
<b>NET WEIGHT</b>	55g
<b>CABLE LENGTH</b>	120CM
<b>RELATIVE HUMIDITY</b>	≤85%