



型号说明

RM-EBB-R-2006-M-L300-00A(H)

插头

包塑式

系列名称

公端

线长300mm

通用型环保产品

产品插针数量
功率针2pin,
信号针6pin

未注公差/General tolerances(mm)	
0	>3
~	>6
3	>10
6	>18
10	>30
18	>50
30	>80
50	>120
80	>180
120	>250
180	>315
250	>400
315	>500
400	>630
500	>800
±0.12	±0.18
±0.22	±0.31
±0.37	±0.57
±0.80	±1.05
±1.15	±1.60
±2.20	±2.50
0.1/10	1/10
1/10	1/10

额定电压/Rated Voltage	110VDC/60A
电流/Current	≥100mA
绝缘电阻/Insulation resistance	≥100MΩ
插拔次数/Mechanical locking life(including cycles)	3000
耐电压/Withstanding voltage	500V AC
使用温度范围/Operating temperature(°C)	-40~+105
防水等级/Levels of protection	—
接线方式/Terminal	Soldering
导线外径范围/Wire range(mm)	10~12

SURFACE: /

MATERIAL: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRT: Huangju 2021.8.20

DEGSON 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: RM-EBBL-2105-M-L300-00A(H)

DRAWING NO.: RM-EBBL-2105-M-L300-00A(H)

REV	ECN	DESCRIPTION	DRKT	20MMXXX	X
10			XX		X

REV	T0
1/1	1/1

TYPE: CUSTOMER DRAWING SCALE: 2:1 SHEET 1/1