

“GuosaiA+” 系注册商标，属乐清市国赛科技发展有限公司所有



本广告资料由国赛科技印制，仅用于展示本企业系列的新产品资料，本手册只汇集了国赛科技部分代表性产品，国赛科技部分产品正在变更，升级版采用更新的生产工艺改进本手册的有关内容，或对本手册的印刷错误及相关资料信息进行必要的改正或更新时，恕不另行通知，敬请留意，敬请谅解。

新目录发行，旧目录自动作废！

This manual is printed by guosai technology, only used to show the relative information of this series. guosai technology keep the right of amending this manual due to technical improved or new production processed, or mistake amended etc without notice. Please contact with our company to confirm the relative information when place the order.

New catalog distribution, old directory automatic abolition

国赛接线端子 GS TERMINAL 2018

GuosaiA+ 國賽



TERMINAL
接线端子



扫一扫 公众号



深圳市国赛科技发展有限公司

SHENZHEN GUOSAI TECHNOLOGY DEVELOPMENT CO., LTD.

公司地址：深圳市福田区振中路新亚洲电子商城4A026

Company Add: A4026 New Asian Electronic Mall,

Zhenzhong road, Futian, Shenzhen, China.

Tel: 0755-61306777 Fax: 0755-61306203

展销地址：深圳市华强北路1015号华强电子世界三号楼B054

Huaqiang North Road, Futian, Shenzhen, China.

Sales Add: B054 Huaqiang electronic world, 1015th

http://www.szguosai.com QQ: 3432352545

E-mail: szgsk@hotmail.com

乐清市国赛科技发展有限公司

YUEQING GUOSAI TECHNOLOGY DEVELOPMENT CO., LTD.

新厂地址：浙江省乐清经济开发区纬十五路202号

Factory Add: No. 202 Wei fifteen Road,

Economic Development Zone, Yueqing, Zhejiang

工厂地址：浙江省乐清市北白象镇马路角工业区

Belbaixiang, Yueqing, Zhejiang

P.C.: 325604

Tel: 0577-61891155 Fax: 0577-61891159

http://www.guosai.cc QQ: 2628462568



中文域名：www.国赛.com

E-mail: guosai@guosai.cc



品质为基 全球服务
Quality Based Serve The World

GUOSAI公司保留对产品规格及技术资料的更新，恕不事先通知，敬请谅解！


PVC绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

**Vinyl-Insulated Ring Terminal
(Apply in flexible wire)**


- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin


RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color		
						W	L	F	E	Dφ		dφ	
RV0.5-3	0.2-0.75 (24-18)	0.5	10A	#4	3.2	5.7	18.3	5.4	2.7	1.3	黄 yellow		
RV0.5-3.5S				#6	3.7	5.7	18.3	5.4	10.0	2.7		1.3	
RV0.5-3.5M				#6	3.7	6.6	19.9	6.3	6.6	19.9		6.3	
RV0.5-4				#8	4.3	6.6	19.9	6.3	6.6	19.9		6.3	

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	Dφ		dφ
RV1.25-3	0.5-1.5 (22-16)	0.75	19A	#4	3.2	5.7	17.8	4.9	4.2	1.7	红 red	
RV1.25-3.5S				#6	3.7	5.7	17.8	4.9				
RV1.25-3.5M				#6	3.7	6.6	20.1	6.3				
RV1.25-3.5L				#6	3.7	8.0	21.5	7.6				
RV1.25-4S				#8	4.3	6.6	20.1	6.3				
RV1.25-4L				#8	4.3	8.0	21.5	7.0				
RV1.25-5S				#10	5.3	8.0	21.5	7.0				
RV1.25-5L				#10	5.3	9.8	23.0	7.6				
RV1.25-6S				1/4	6.4	9.8	23.0	7.6				
RV1.25-6L				1/4	6.4	11.6	27.5	11.1				
RV1.25-8				5/16	8.4	11.6	27.5	11.1				
RV1.25-10				3/8	10.5	13.6	31.6	13.9				
RV1.25-12	1/2	13.0	19.2	36.0	16.5							

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	Dφ		dφ
RV2-3	1.5-2.5 (16-14)	0.8	27A	#4	3.2	6.6	18.5	4.3	4.9	2.3	蓝 blue	
RV2-3.5S				#6	3.7	6.6	18.5	4.7				
RV2-3.5M				#6	3.7	6.6	20.0	6.0				
RV2-3.5L				#6	3.7	8.5	22.5	7.7				
RV2-4S				#8	4.3	6.6	20.0	6.5				
RV2-4L				#8	4.3	8.5	22.5	7.7				
RV2-5S				#10	5.3	8.5	22.5	7.7				
RV2-5L				#10	5.3	9.5	22.5	7.0				
RV2-6S				1/4	6.4	9.5	22.5	7.0				
RV2-6L				1/4	6.4	12.0	27.6	11.0				
RV2-8				5/16	8.4	12.0	27.6	11.0				
RV2-10				3/8	10.5	14.6	31.2	13.0				
RV2-12	1/2	13.0	19.2	35.7	15.5							


PVC绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

**Vinyl-Insulated Ring Terminal
(Apply in flexible wire)**



- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin


RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	Dφ		dφ
RV3.5-4	2.5-4 (14-12)	1.0	37A	#8	4.3	8.0	25.3	7.7			黑 black	
RV3.5-5S				#10	5.3	8.0	25.3	7.7				
RV3.5-5L				#10	5.3	12.0	27.9	9.3				
RV3.5-6				1/4	6.4	12.0	29.0	9.3				
RV3.5-8				5/16	8.4	15.0	35.0	14				
RV3.5-10				3/8	10.5	15.0	34.6	14				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	Dφ		dφ
RV5.5-3	4-6 (12-10)	1.0	48A	#4	3.2	7.2	22.7	6.1			黄 yellow	
RV5.5-3.5				#6	3.7	7.2	22.7	5.9				
RV5.5-4S				#8	4.3	7.2	22.7	5.9				
RV5.5-4L				#8	4.3	9.5	26.3	8.3				
RV5.5-5				#10	5.3	9.5	26.3	8.3				
RV5.5-6				1/4	6.4	12.0	30.0	11.0				
RV5.5-8				5/16	8.4	15.0	34.7	13.7				
RV5.5-10				3/8	10.5	15.0	34.7	13.7				
RV5.5-12				1/2	13.0	19.2	39.0	16.0				

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)					颜色 Color	
						W	L	F	E	Dφ		dφ
RV8-4	6.0-10 (8)	1.2	62A	#8	4.3	8.8	32.3	11.0			红 red	
RV8-5S				#10	5.3	8.8	32.3	13.3				
RV8-5M				#10	5.3	12.0	32.3	9.3				
RV8-5L				#10	5.3	15.0	38.3	13.8				
RV8-6S				1/4	6.4	12.0	32.3	9.8				
RV8-6L				1/4	6.4	15.0	38.3	13.8				
RV8-8				5/16	8.4	15.0	38.3	13.8				
RV8-10				3/8	10.5	15.0	38.3	13.8				
RV8-12				1/2	13.0	22.0	48.0	20.5				




尼龙绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105°C
 - 表面处理: 镀锌
- Nylon-Insulated Ring Terminal
(Apply in flexible wire)**
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105°C
 - Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color	
						W	L	F	E		Dφ
RVN 1.25-3				#4	3.2	5.7	18.5	4.9			
RVN 1.25-3.5S				#6	3.7	5.7	18.5	4.9			
RVN 1.25-3.5M				#6	3.7	6.6	20.8	6.3			
RVN 1.25-3.5L				#6	3.7	8.0	22.2	7.6			
RVN 1.25-4S				#8	4.3	6.6	20.8	6.3			
RVN 1.25-4L				#8	4.3	8.0	22.2	7.0			
RVN 1.25-5S	0.5-1.5 (22-16)	0.75	19A	#10	5.3	8.0	22.2	7.0	11.0	4.3	1.7
RVN 1.25-5L				#10	5.3	9.8	23.7	7.6			
RVN 1.25-6S				1/4	6.4	9.8	23.7	7.6			
RVN 1.25-6L				1/4	6.4	11.6	28.2	11.1			
RVN 1.25-8				5/16	8.4	11.6	28.2	11.1			
RVN 1.25-10				3/8	10.5	13.6	32.3	13.9			
RVN 1.25-12				1/2	13.0	19.2	36.7	16.5			



尼龙绝缘护套圆形端子(适用于软线)


- 材质: 紫铜
 - 护套: 尼龙
 - 温度: 105°C
 - 表面处理: 镀锌
- Nylon-Insulated Ring Terminal
(Apply in flexible wire)**
- Terminal Body: Copper
 - Insulation: Nylon
 - Temperature: 105°C
 - Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color	
						W	L	F	E		Dφ
RVN 3.5-4				#8	4.3	8.0	25.2	7.7			
RVN 3.5-5S				#10	5.3	8.0	25.2	7.7			
RVN 3.5-5L				#10	5.3	12.0	27.3	9.3			
RVN 3.5-6	2.5-4.0 (14-12)	1.0	37A	1/4	6.4	12.0	28.6	9.3	13.3	6.0	3.0
RVN 3.5-8				5/16	8.4	15.0	34.2	14			
RVN 3.5-10				3/8	10.5	15.0	34.2	14			

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺柱口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color	
						W	L	F	E		Dφ
RVN 5.5-3				#4	3.2	7.2	23.0	5.9			
RVN 5.5-3.5				#6	3.7	7.2	23.0	5.9			
RVN 5.5-4S				#8	4.3	7.2	23.0	5.9			
RVN 5.5-4L				#8	4.3	9.5	26.5	8.3			
RVN 5.5-5	4-6 (12-10)	1.0	48A	#10	5.3	9.5	26.5	8.3	14.0	6.6	3.4
RVN 5.5-6				1/4	6.4	12.0	30.3	11.0			
RVN 5.5-8				5/16	8.4	15.0	34.7	13.7			
RVN 5.5-10				3/8	10.5	15.0	34.7	13.7			
RVN 5.5-12				1/2	13.0	19.2	39.5	16.0			



尼龙绝缘护套圆形端子(加铜套)(适用于软线)

- 材质: 紫铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

Nylon-Insulated Ring Terminal(Double Copper Sleeve)
(Apply in flexible wire)


- Terminal Body: Copper
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color	
						W	L	F	E		Dφ
RVN 1.25-3-D				#4	3.2	5.7	18.5	4.9			
RVN 1.25-3.5S D				#6	3.7	5.7	18.5	4.9			
RVN 1.25-3.5M D				#6	3.7	6.6	20.8	6.3			
RVN 1.25-3.5L D				#6	3.7	8.0	22.2	7.6			
RVN 1.25-4S D				#8	4.3	6.6	20.8	6.3			
RVN 1.25-4L D				#8	4.3	8.0	22.2	7.0			
RVN 1.25-5S D	0.5-1.5 (22-16)	0.75	19A	#10	5.3	8.0	22.2	7.0	11.0	3.8	1.7
RVN 1.25-5L D				#10	5.3	9.8	23.7	7.6			
RVN 1.25-6S D				1/4	6.4	9.8	23.7	7.6			
RVN 1.25-6L D				1/4	6.4	11.6	28.2	11.1			
RVN 1.25-8 D				5/16	8.4	11.6	28.2	11.1			
RVN 1.25-10 D				3/8	10.5	13.6	32.3	13.9			
RVN 1.25-12 D				1/2	13.0	19.2	36.7	16.5			

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color	
						W	L	F	E		Dφ
RVN 2-3-D				#4	3.2	6.6	19.0	4.3			
RVN 2-3.5S D				#6	3.7	6.6	19.2	4.7			
RVN 2-3.5M D				#6	3.7	6.6	20.5	6.0			
RVN 2-3.5L D				#6	3.7	8.5	23.0	7.7			
RVN 2-4S D				#8	4.3	6.6	20.5	6.5			
RVN 2-4L D				#8	4.3	8.5	23.0	7.7			
RVN 2-5S D	1.5-2.5 (16-14)	0.8	27A	#10	5.3	8.5	23.0	7.7	11.0	4.4	2.3
RVN 2-5L D				#10	5.3	9.5	23.0	7.0			
RVN 2-6S D				1/4	6.4	9.5	23.0	7.0			
RVN 2-6L D				1/4	6.4	12.0	28.1	11.0			
RVN 2-8 D				5/16	8.4	12.0	28.1	11.0			
RVN 2-10 D				3/8	10.5	14.6	31.7	13.0			
RVN 2-12 D				1/2	13.0	19.2	36.2	15.5			



尼龙绝缘护套圆形端子(加铜套)(适用于软线)

- 材质: 紫铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

Nylon-Insulated Ring Terminal(Double Copper Sleeve)
(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color	
						W	L	F	E		Dφ
RVN 3.5-4-D				#8	4.3	8.0	25.2	7.7			
RVN 3.5-5S D				#10	5.3	8.0	25.2	7.7			
RVN 3.5-5L D	2.5-4.0 (14-12)	1.0	37A	#10	5.3	12.0	27.6	9.3			
RVN 3.5-6 D				1/4	6.4	12.0	28.6	9.3	13.3	5.4	3.0
RVN 3.5-8 D				5/16	8.4	15.0	34.2	14			
RVN 3.5-10 D				3/8	10.5	15.0	34.2	14			

型号 Item NO	导线截面mm ² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)				颜色 Color	
						W	L	F	E		Dφ
RVN 5.5-3-D				#4	3.2	7.2	23.0	6.1			
RVN 5.5-3.5 D				#6	3.7	7.2	23.0	5.9			
RVN 5.5-4S D				#8	4.3	7.2	23.0	5.9			
RVN 5.5-4L D				#8	4.3	9.5	26.5	8.3			
RVN 5.5-5 D	4-6 (12-10)	1.0	48A	#10	5.3	9.5	26.5	8.3	14.0	6.1	3.4
RVN 5.5-6 D				1/4	6.4	12.0	30.3	11.0			
RVN 5.5-8 D				5/16	8.4	15.0	34.7	13.7			
RVN 5.5-10 D				3/8	10.5	15.0	34.7	13.7			
RVN 5.5-12 D				1/2	13.0	19.2	39.5	16.0			