


未注公差/General tolerances(mm)	
0 ~ 3	>3 ~ 6
>6 ~ 10	>10 ~ 18
>18 ~ 30	>30 ~ 50
>50 ~ 80	>80 ~ 120
>120 ~ 180	>180 ~ 250
>250 ~ 315	>315 ~ 400
>400 ~ 500	>500 ~ 630
>630 ~ 800	>800 ~ 1000
>1000	>1000

未标注尺寸请参考3D文件

推荐面板安装尺寸
推荐面板厚度最大5mm



型号说明

SA-EBBM-2003-F-00A(H)

- 插座
- 组装式
- 系列名称
- 产品插针数量
功率针 2pin,
PE针 1pin,
信号针 5pin
- 母端
- 通用型环保产品

额定电压/Rated Voltage	80V/20A
额定电流/Rated Current	80V/20A
绝缘电阻/Insulation resistance	≥100MΩ
插拔次数/Mechanical working life(fading cycles)	3000
耐电压/Withstanding voltage	500V AC
使用温度范围/Operating temperature(°C)	-40~+85
防水等级/Levels of protection	IP67(Single)
接线方式/Terminal	Soldering

SURFACE: /

DEGSON 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: SA-EBBM-2003-F-00A(H)

MATERIAL: /	MAT NO.: /	STATUS: /	APPD: /	CHKD: /	DRT: Huangju 2021.8.20	SIZE: A4	SCALE: 2:1	REV: T0
DESCRIPTION: A0	DRKT: 20MMX30MM	DRFT: Huangju 2021.8.20	DRAWING NO.: SA-EBBM-2003-F-00A(H)	TYPE: CUSTOMER DRAWING	SCALE: 2:1	SHEET: 1/1	REV: T0	1/1