



WEBSITE PHOTOS

⚠ This dwg is for reference only, Actual dwg should be based on formal engineering dwg issued by Kang Yang.



A	B	C
10.0	4.2	6.3


 康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN) CO., LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.
ISO 9001
ISO 14001
QC 080000

PART NUMBER		4-10	SPEC. DWG.	
TITLE				
ROUND SPACER				
MATERIAL			COLOR	
NYLON 66(UL) 94V-0			BLACK	
SIZE	SCALE	UNIT	CHECK	
A4	2:1	mm	Z.C	

PART NO	A	B	C
4-2	2.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-3	3.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-3.5	3.5	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-4	4.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-4.83	4.83	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-5	5.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-6	6.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-7	7.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-7.5	7.5	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-8	8.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-8.5	8.5	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-9	9.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-9.5	9.5	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-11	11.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			



PART NO	A	B	C	
4-12	12.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-12.7	12.7	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-13	13.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-14	14.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-15	15.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-16	16.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-17	17.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-18	18.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-19	19.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-20	20.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-21	21.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-22	22.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-23	23.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
4-24	24.0	4.2	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.



PART NO	A	B	C
4-25	25.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-26	26.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-27	27.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-28	28.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-28.7	28.7	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-29	29.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-30	30.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-40	40.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-45	45.0	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
4-3.4	3.4	4.2	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			

