






**Modularized accessories which can be installed additionally**

 <p>AX-3 Auxiliary contact</p>	Number of auxiliary contacts	4NO	AX-3/40	Able to be used for the whole series products
		3NO+1NC	AX-3/31	
		2NO+2NC	AX-3/22	
		1NO+3NC	AX-3/13	
		4NC	AX-3/04	
		2NO	AX-3/20	
		1NO+1NC	AX-3/11	
		2NC	AX-3/02	
 <p>F5 1N/O+1N/C Air delay head</p>	On-delay time (s)	0.1~3	F5-T0	Able to be used for the whole series products
		0.1~30	F5-T2	
		10~180	F5-T4	
		0.1~3	F5-D0	
	Off-delay time (s)	0.1~30	F5-D2	
		10~180	F5-D4	
 <p>NCF1-11C Secondary side suspension auxiliary contact</p>	Number of auxiliary contacts	1NO+1NC	NCF1-11C	Able to be used for the products of 170A or lower
 <p>SR2-A Surge suppressor</p>	Suppression voltage range	AC 24V~48V	SR2 24V~48V	ble to be used for the products of 9A~38A or lower
		AC 100V~250V	SR2 100V~250V	
		AC 380V~440V	SR2 380V~440V	
 <p>SR2-B Surge suppressor</p>		AC 100V~127V	SR2-B 100V~127V	ble to be used for the products of 40A~95A or lower
		AC 200V~250V	SR2-B 200V~250V	
		AC 380V~440V	SR2-B 380V~440V	