





The highly reliable low cost TES regulator protects deep cycle batteries from over charging and excessive discharging.

Suitable for all 12 volt systems and has a Load shed of up to 60 amp continuously. The regulator accepts a range of current between 0 to 60Amps.

STATE-OF-CHARGE WITH LED INDICATION AND LCD DISPLAY	
	Battery full / Panel is disconnected from the battery
	Battery Half / Load and panel connected to the battery
	Battery voltage low/ Load disconnected

TECHNICAL SPECIFICATIONS	
System Voltage (Voc)	12V
Solar module current (Isc)	60A
Max Load Current	60A
End of charge Voltage	14.0V
Reconnection Voltage	13.0V
Load Disconnect Voltage	11.0V
Load Reconnect Voltage	12.0V

GENERAL INFORMATION	
Weight(g)	520
Dimensions (W x H x D)	110 x 155 x 43mm
Max. self consumption	< 0.5W
Ambient temperature range	-20 to +60 degree C
Max. conductor size for terminals	22.14 AWG
Enclosure protection	IP 22
Mounting bracket screw size	4mm
Warranty	1 year



****NB: ALWAYS CONNECT YOUR BATTERY TO YOUR REGULATOR FIRST****

CONTACT US

98 Bofors Circle, Epping Ind. 2
Cape Town, South Africa, 7460
Tel: 021 535 1978 or 021 535 1741
Fax: 021 535 1651 or 021 535 2084
Int: +27 21 535 1978
info@setsolar.co.za
www.setsolar.co.za