

PVC绝缘护套叉形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Spade Terminal

(Apply in flexible wire)


- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin



SPADE TERMINAL

| 型号<br>Item NO | 导线截面mm <sup>2</sup><br>Cable Size<br>A.W.G | 材料厚度<br>Thickness<br>(mm) | 最大电流<br>Max Current | 美制螺栓号<br>USA Screw | 螺栓口直径<br>Screw Dia.<br>d2(mm) | 尺寸Dimension(mm) |      |      |      |     | 颜色<br>Color |             |
|---------------|--|---------------------------|---------------------|--------------------|-------------------------------|-----------------|------|------|------|-----|-------------|-------------|
|               |  |                           |                     |                    |                               | W               | L    | F    | E    | DΦ  |             | dΦ          |
| SV 0.5-3      | 0.2-0.75<br>(24-18)                        | 0.5                       | 10A                 | #4                 | 3.2                           | 5.7             | 19.5 | 5.1  | 10.0 | 2.7 | 1.3         | 黄<br>yellow |
| SV 0.5-4      |  |                           |                     | #8                 | 4.3                           | 6.4             | 19.5 | 5.3  |      |     |             |             |
| 型号<br>Item NO | 导线截面mm <sup>2</sup><br>Cable Size<br>A.W.G | 材料厚度<br>Thickness<br>(mm) | 最大电流<br>Max Current | 美制螺栓号<br>USA Screw | 螺栓口直径<br>Screw Dia.<br>d2(mm) | 尺寸Dimension(mm) |      |      |      |     | 颜色<br>Color |             |
| SV 1.25-3     |  |                           |                     | #4                 | 3.2                           | 5.7             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-3.5S  |  |                           |                     | #6                 | 3.7                           | 5.7             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-3.5L  |  |                           |                     | #6                 | 3.7                           | 6.4             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-4S    |  |                           |                     | #8                 | 4.3                           | 6.4             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-4M    | 0.5-1.5<br>(22-16)                         | 0.75                      | 19A                 | #8                 | 4.3                           | 7.2             | 21.8 | 6.5  | 10.7 | 4.2 | 1.7         | 红<br>red    |
| SV 1.25-4L    |  |                           |                     | #8                 | 4.3                           | 8.1             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-5S    |  |                           |                     | #10                | 5.3                           | 8.1             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-5L    |  |                           |                     | #10                | 5.3                           | 9.3             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-6S    |  |                           |                     | 1/4                | 6.4                           | 9.5             | 21.8 | 6.5  |      |     |             |             |
| SV 1.25-6L    |  |                           |                     | 1/4                | 6.4                           | 12.0            | 28.0 | 11.0 |      |     |             |             |

| 型号<br>Item NO | 导线截面mm <sup>2</sup><br>Cable Size<br>A.W.G | 材料厚度<br>Thickness<br>(mm) | 最大电流<br>Max Current | 美制螺栓号<br>USA Screw | 螺栓口直径<br>Screw Dia.<br>d2(mm) | 尺寸Dimension(mm) |      |      |      |     | 颜色<br>Color |           |
|---------------|--|---------------------------|---------------------|--------------------|-------------------------------|-----------------|------|------|------|-----|-------------|-----------|
|               |  |                           |                     |                    |                               | W               | L    | F    | E    | DΦ  |             | dΦ        |
| SV 2-3        |  |                           |                     | #4                 | 3.2                           | 5.7             | 21.7 | 6.5  |      |     |             |           |
| SV 2-3.5S     |  |                           |                     | #6                 | 3.7                           | 5.7             | 21.7 | 6.5  |      |     |             |           |
| SV 2-3.5L     |  |                           |                     | #6                 | 3.7                           | 6.2             | 21.7 | 6.5  |      |     |             |           |
| SV 2-4S       |  |                           |                     | #8                 | 4.3                           | 6.4             | 21.7 | 6.5  |      |     |             |           |
| SV 2-4M       | 1.5-2.5<br>(16-14)                         | 0.8                       | 27A                 | #8                 | 4.3                           | 7.2             | 21.7 | 6.5  | 10.7 | 4.9 | 2.3         | 蓝<br>blue |
| SV 2-4L       |  |                           |                     | #8                 | 4.3                           | 8.1             | 21.7 | 6.5  |      |     |             |           |
| SV 2-5S       |  |                           |                     | #10                | 5.3                           | 8.1             | 21.7 | 6.5  |      |     |             |           |
| SV 2-5L       |  |                           |                     | #10                | 5.3                           | 9.5             | 21.7 | 6.5  |      |     |             |           |
| SV 2-6S       |  |                           |                     | 1/4                | 6.4                           | 9.5             | 21.7 | 6.5  |      |     |             |           |
| SV 2-6L       |  |                           |                     | 1/4                | 6.4                           | 12.0            | 27.7 | 11.0 |      |     |             |           |



PVC绝缘护套叉形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Spade Terminal

(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin



SPADE TERMINAL

| 型号<br>Item NO | 导线截面mm <sup>2</sup><br>Cable Size<br>A.W.G | 材料厚度<br>Thickness<br>(mm) | 最大电流<br>Max Current | 美制螺栓号<br>USA Screw | 螺栓口直径<br>Screw Dia.<br>d2(mm) | 尺寸Dimension(mm) |      |      |      |     | 颜色<br>Color |             |
|---------------|--|---------------------------|---------------------|--------------------|-------------------------------|-----------------|------|------|------|-----|-------------|-------------|
|               |  |                           |                     |                    |                               | W               | L    | F    | E    | DΦ  |             | dΦ          |
| SV 3.5-3      |  |                           |                     | #4                 | 3.2                           | 5.7             | 25.8 | 7.0  |      |     |             |             |
| SV 3.5-4S     |  |                           |                     | #8                 | 4.3                           | 7.2             | 25.8 | 7.0  |      |     |             |             |
| SV 3.5-4      | 2.5-4<br>(14-12)                           | 1.0                       | 37A                 | #8                 | 4.3                           | 8.0             | 25.8 | 7.0  | 13.8 | 5.8 | 3.0         | 黑<br>black  |
| SV 3.5-5      |  |                           |                     | #10                | 5.3                           | 8.0             | 25.8 | 7.0  |      |     |             |             |
| SV 3.5-6      |  |                           |                     | 1/4                | 6.4                           | 12.0            | 28.8 | 8.7  |      |     |             |             |
| 型号<br>Item NO | 导线截面mm <sup>2</sup><br>Cable Size<br>A.W.G | 材料厚度<br>Thickness<br>(mm) | 最大电流<br>Max Current | 美制螺栓号<br>USA Screw | 螺栓口直径<br>Screw Dia.<br>d2(mm) | 尺寸Dimension(mm) |      |      |      |     | 颜色<br>Color |             |
| SV 5.5-3.5    |  |                           |                     | #6                 | 3.7                           | 7.2             | 24.8 | 7.5  |      |     |             |             |
| SV 5.5-4S     |  |                           |                     | #8                 | 4.3                           | 8.3             | 26.0 | 7.5  |      |     |             |             |
| SV 5.5-4L     |  |                           |                     | #8                 | 4.3                           | 9.0             | 26.0 | 7.5  |      |     |             |             |
| SV 5.5-5      | 4-6<br>(12-10)                             | 1.0                       | 48A                 | #10                | 5.3                           | 9.0             | 26.0 | 7.5  | 13.6 | 6.4 | 3.4         | 黄<br>yellow |
| SV 5.5-6S     |  |                           |                     | 1/4                | 6.4                           | 9.0             | 26.0 | 7.5  |      |     |             |             |
| SV 5.5-6L     |  |                           |                     | 1/4                | 6.4                           | 12.0            | 32.0 | 12.0 |      |     |             |             |
| SV 5.5-8      |  |                           |                     | 5/16               | 8.4                           | 14.0            | 30.8 | 11.5 |      |     |             |             |

| 型号<br>Item NO | 导线截面mm <sup>2</sup><br>Cable Size<br>A.W.G | 材料厚度<br>Thickness<br>(mm) | 最大电流<br>Max Current | 美制螺栓号<br>USA Screw | 螺栓口直径<br>Screw Dia.<br>d2(mm) | 尺寸Dimension(mm) |      |     |      |     | 颜色<br>Color |          |
|---------------|--|---------------------------|---------------------|--------------------|-------------------------------|-----------------|------|-----|------|-----|-------------|----------|
|               |  |                           |                     |                    |                               | W               | L    | F   | E    | DΦ  |             | dΦ       |
| SV 8-4        | 6-10<br>(8)                                | 1.2                       | 62A                 | #8                 | 4.3                           | 8.7             | 30.8 | 9.1 |      |     |             | 红<br>red |
| SV 8-5        |  |                           |                     | #10                | 5.3                           | 11.0            | 31.8 | 8.3 | 17.0 | 8.0 | 4.5         |          |
| SV 8-6        |  |                           |                     | 1/4                | 6.3                           | 12.0            | 32.8 | 8.7 |      |     |             |          |