



20 Cocopan Crescent, Driehoek, Germiston  
Gauteng, South Africa  
Tel: +27 11 873 1311 FAX: +27 11 873 2396  
Web: www.eurocel.it

## PRODUCT INFORMATION

# EUROCEL SECURITY PRINTED TAPE

### DESCRIPTION

Single sided under surface printed warning tape.

### PRODUCT DATA

Backing	0.025mm Printed BOPP Film
Adhesive	Synthetic rubber and resins hot melt based

	Unit	Average Value	Method
Total thickness	mm	0.043	PSTC 133
Adhesion to steel	N/25mm	13.75	PSTC 101
Tensile strength MD	N/25mm	87	PSTC 131
Elongation at break	%	150	PSTC 131
Temp. Resistance	°C	60°C	=

### APPLICATION

Printed warning tape. Standard carton sealing tape, suitable for most common use.

Features	Benefits	
Synthetic rubber and resins hot melt based adhesive	✓ High tack	✓ Performing well in most common use
Printed BOPP backing	✓ Well adaptable to different shapes	✓ Good elongation

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; based on the product being stored at 15°C to 25°C with max. relative humidity of 65% out of direct sunlight. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature is lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.