




RECOMMEND P. C. B LAYOUT
PCB TOLERANCE: ±0.05 (TOP VIEW)



SPECIFICATIONS

Current Rating:	1.5 Amps
Insulation Resistance:	1000MΩ Min
Contact Resistance:	20mΩ Max
Withstanding Voltage:	AC 500V
Operation Temperature:	-40° to +105°
Contact Material:	Brass
Standard:	PA6T
Insulator Material:	Polyester (UL 94V-0)
Contact Plating:	Gold Flash
Max. Processing Temp:	240° C for 30-60seconds (260° C for 5seconds)

Code Description

200-PH-1-XX-20-S-87-1-G0-B

(1) (2) (3) (4) (5) (6) (7) (8) (9) (10)

- Pin Spacing: 200±0.3mm
- Product Name: PH-Pin Header
- No. of Rows: 1=Single Row; 2=Dual Row
- No. of Pins Per Row: 1~40
- Insulator Material Height: 15=1.5mm; 20=2.0mm
- Connector Type: S=Straight; R=Right; Angle R=SMT
- Contact Material Length: 87=8.7mm; 105=10.5mm
- No. of Insulator Material: 1=1PCS; 2=2PCS; 3=3PCS
- Contact Plating:
 SS=Flux; G0=Gold Flash; S0=Gold Flash/Tin; M08=to 0.8μ"
- Insulator Material Option:
 A=FR-1BT; B=FR-PA6T; C=FR-PA46; D=FR-LCP; S=Special