

**0.36inch DC4.5-30V, Red Digital Display Voltage Meter SUNLEPHANT
P/N:200390**



TWO WIRES 0.36 INCH VOLTMETER

REVERSE CONNECT PROTECTION

Three color available

TESTING RANGE

DC4.5V-30V

SUNLEPHANT

Mode : DSN-DVML-368-2

- High accuracy
- Low start working voltage , Red 4.5V lowest , green 4.7V lowest , blue 5V lowest.
- Have reverse connect protection.

Technical Parameter:

Testing range	RED DC4.50-30.0V, GREEN DC4.70-30.0V, BLUE DC5.00-30.0V
---------------	---

Power supply range	Use directly from testing voltage as power
The highest input	DC30.0V。 Note: Input higher than 30V may be damaged permanently.
Allow errors	±1%
Input impedance	> 100KΩ
Working current	Red < 23mA, Green< 18mA, Blue< 13mA
Refresh rate	About 300mS once
Display type	Three position 0.36" LED nixie tube
Display color	Red ,green, blue
Lead length	15cm
External size	23 x 15 x 10 mm, L*W*H (exclude installed ear) ; Include installed ear: 33mm
Installed hole	Hole distance: 28mm, Hole diameter: 2.8mm
Net weight	4.7g
Gross weight	5.3g
Working temperature	-10°C~65°C