


Item no.: 236-401  
 Product description: MODULAR PCB TERMINAL BLOCK 2 SOLDER PINS / POLE  
 1 POLE PIN SPACING 5/5.08 MM / 0.2 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 600 6\*100 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	0.877 g
Color	gray
No. of connection Points	1
No. of potentials	1
pole count	1
Height	13 mm
Height	0.512 in
Width	5 mm
Width	0.197 in
Depth	14 mm
Depth	0.551 in
Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV

Current intensity EN  
Pollution degree  
Measured voltage EN

24 A  
2  
630 V



Measured shock voltage	4 kV
Current intensity EN	24 A
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>
Wiring method	solid
Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>
Cross section [mm <sup>2</sup> ]	0.25 - 1.5 mm <sup>2</sup>
Cross section [mm <sup>2</sup> ]	0.25 - 1.5 mm <sup>2</sup>
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I
xxx-xxx/332-000	with 2 solder pins/pole and 5,5 mm long solder pins



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
236-401	BV	11915/BO	500/250	16	0,08-2,5
236-401	CCA	NL6247	250	24	0,08-2,5
236-401	CSA	154112-1673957	300	15	28-12
236-401	DNV	E-9215	250	16	0,5-2,5
236-401	GL	17296-00HH	500/250	16	0,5-2,5
236-401	KEMA	2110204.01	250	24	0,08-2,5
236-401	RMR	11130002	250	16	0,5-2,5
236-401	UR	E45172	300	10	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected