


# 3.00mm (.118") Pitch Micro-Fit 3.0™ Terminal, Female- 43030



## Features and Benefits

- 4 points of contact for optimum reliability
- Box-type spring contact for high normal force
- Locking tong secures terminal in housing



## Reference Information

- Product Specification: **PS-43045**
- Packaging: **Loose or chain**
- Tooling Information: **See Table**
- UL File No.: **E29179**
- CSA File No.: **LR19980**
- Use With: [Receptacle 43025](#)
- Designed In: **Millimeters**

## Electrical

- Voltage: **250V**
- Current: **5.0A max.**
- Contact Resistance: **10mΩmax.**

## Physical

- Contact: **Phosphor Bronze**
- Plating: **Tin or Gold**

### [Top, Front, Side View](#)

<b>ORDERING INFORMATION AND DIMENSIONS</b>								
Wire Size AWG	Plating	Order No.		Dimension				TM-40
		Chain	Loose	C	D	E	F	
20-24	Tin	*43030-0001	*43030-0007	2.29(.090)	2.54(.100)	1.91(.075)	2.08(.082)	11-40-
26-30		*43030-0004	*43030-0010	1.91(.075)	2.10(.083)	1.47(.058)	1.65(.065)	11-40-
20-24	15μ"Gold	*43030-0002	*43030-0008	2.29(.090)	2.54(.100)	1.91(.075)	2.08(.082)	11-40-
26-30		*43030-0005	*43030-0011	1.91(.075)	2.10(.083)	1.47(.058)	1.65(.065)	11-40-
20-24	30μ Gold	*43030-0003	*43030-0009	2.29(.090)	2.54(.100)	1.91(.075)	2.08(.082)	11-40-
26-30		*43030-0006	*43030-0012	1.91(.075)	2.10(.083)	1.47(.058)	1.65(.065)	11-40-

\* US Standard Product, available through Molex franchised distributors

