

**«Jumbo» indicator
waterproof IP65**
**«Jumbo» Leuchte
wasserdicht IP65**
**Lampe «Jumbo»
étanche IP65**

951



Package dimensions All dimensions are in millimeters	Emitted colour	Electro-optical characteristics Ta = 25°C						Viewing angle	Type Typ Type
		Peak Wave-length λp	Operat. Temp.	Stor. Temp.	Luminous intensity I _v Typ.	Forward voltage V _F Typ.	I _F		
		nm	°C	°C	mcd	V	mA		
<p>Material: Lens: Polycarbonat (LEXAN) Body: Thermoplast ABS meet UL94V-0/1,6</p> <p>Flashing versions available in any colour and voltage. Please put a «F» for Flashing at the end of part-number.</p> <p>Blinkende Ausführung erhältlich in allen Farben und Spannungen. Bitte ergänzen Sie ein «F» am Ende der Artikelnummer.</p> <p>Version clignotante sur tout les modèles dans l'ensemble des couleurs et des tensions. Ajouter la lettre «F» à la référence.</p> <p>For example: Green 230VAC flashing (blinking) 951GG3ZF Red 24VAC/DC flashing (blinking) 951RR0DF</p>	Blue Blau Bleu	470			4 LED's à 4800 mcd	12 AC/DC	20	60	951BB3B
						24 AC/DC			951BB3D
						48 AC/DC			951BB3J
						115 AC/DC			951BB3X
						230 AC			951BB3Z
	Green Grün Vert	565			4 LED's à 800 mcd	12 AC/DC	20	60	951GG0B
						24 AC/DC			951GG0D
						48 AC/DC			951GG0J
						115 AC/DC			951GG0X
						230 AC			951GG0Z
		525	super-bright 4 LED's à 16000 mcd	12 AC/DC	20	60	951GG3B		
		24 AC/DC		951GG3D					
		48 AC/DC		951GG3J					
		115 AC/DC		951GG3X					
		230 AC		951GG3Z					
	Red Rot Rouge	660			4 LED's à 3000 mcd	12 AC/DC	20	60	951RR0B
						24 AC/DC			951RR0D
						48 AC/DC			951RR0J
						115 AC/DC			951RR0X
						230 AC/DC			951RR0Z
	White Weiss Blanc	x = 0.31 y = 0.32			super-bright 4 LED's à 9200 mcd	12 AC/DC	20	60	951WW3B
						24 AC/DC			951WW3D
						48 AC/DC			951WW3J
						115 AC/DC			951WW3X
230 AC						951WW3Z			
Yellow Gelb Jaune	585			4 LED's à 250 mcd	12 AC/DC	20	60	951YY0B	
					24 AC/DC			951YY0D	
					48 AC/DC			951YY0J	
					115 AC/DC			951YY0X	
					230 AC/DC			951YY0Z	
	590	super-bright 4 LED's à 8700 mcd	12 AC/DC	20	60	951YY3B			
	24 AC/DC		951YY3D						
	48 AC/DC		951YY3J						
	115 AC/DC		951YY3X						
	230 AC		951YY3Z						

Reserve de modifications de toutes les données techniques
Änderungen die dem technischen Fortschritt dienen, sind vorbehalten
Specifications are subject to change without notice

– Spezial executions on request

– Spezialanfertigungen auf Anfrage

– Executions speciales sur demande