



### SFE American Car Fuse

- Voltage Rating: 32V

Ampere Rating	Size (inch)
4A	1/4 x 5/8
6A	1/4 x 3/4
7.5A	1/4 x 7/8
9A	1/4 x 7/8
14A	1/4 x 1-1/16
20A	1/4 x 1-1/4
30A	1/4 x 1-7/16

- Approval:



### JASO Fast Acting Glass Fuse

- 6.3ø x 30 mm
- Ampere Rating: 0.5A, 1A, 1.5A, 2A, 2.5A, 3A, 4A, 5A, 6A, 7.5A, 10A, 15A, 20A, 25A, 30A, 35A, 40A
- Voltage Rating: 32V and less
- Standards: JASO D601
- Electrical Characteristic:

Rated Current	1 In	1.35 In	1.5 In	2 In
	MIN	MAX	MAX	MAX
0.5A~20A	4 hr	1 hr	15 sec	-
20.1A~40A	4 hr	1 hr	20 sec	-
Above 40A	4 hr	1 hr	-	60 sec




### AST (Mini-Blade Type) Terminal Car Fuse

- Transparent Body
- Voltage Rating: 32V and less

Ampere Rating	Body Color
2A	Gray
3A	Violet
4A	Pink
5A	Tan
7.5A	Brown
10A	Red
15A	Lt. Blue
20A	Yellow
25A	Natural
30A	Lt. Green

- Equivalent MIN and ATM Fuse

RoHS



### ATQ (Blade Type) Terminal Car Fuse

- Transparent Body
- Voltage Rating: 32V and less

Ampere Rating	Body Color
2A	BlackishGreen
3A	Violet
4A	Pink
5A	Tan
7.5A	Brown
10A	Red
15A	Lt. Blue
20A	Yellow
25A	Natural
30A	Lt. Green
35A	Purple

- Equivalent ATQ and ATC Fuse

RoHS

