



REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

NOTES1:  
 UL Standard  
 1.Torque value : M2.5 , 5.0Lb.in  
 2.Wire range : 26~12AWG

IEC Standard

1.

Pollution degree	3
Overtoltage category	III
Rate impulse voltage(KV)	/
Rate voltage(V)	/ V
Rate current(A)	/ A

2.Torque value : M2.5 , 0.4N·m  
 3.Wire range : 0.2~2.5mm?

NOTES2:  
 1.Dimension shall be interpreted per ASME Y14.5-2009  
 2.Stripping length : 8~9mm  
 3.Operating temperature: -40°C~+105°C  
 4.Undimensioned tolerances:

Pitch		Range In		Nominal Dimension Range				D
mm	In	In	mm	In	mm	In		
TO	TO	Over 6 TO 10	Over 10 TO 24	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150	0.1/10
6	10	10	24	30	60	100	150	<
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2'

5.RoHS Compliance

仅供参考图  
 2016.07.14

ITEM	NAME OF PART	MATERIAL	NOTES
5	GROUNDING	PHOSPHOR BRONZE	Zn Plated
4	CAGE	STEEL	M2.5/Zn Plated
3	CURRENT CARRIER	COPPER	Zn Plated
2	SCREW	STEEL	M2.5/Zn Plated
1	HOUSING	PA66	UL94V-0

DETACHED LISTS	PART NO.:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
	APPD: <i>Almo/14/16</i>	NAME: DC2.5-PE-01P-1C-00A(H)		
	CHKD:	TITLE: CUSTOMER DRAWING		
	DRFT: XMY 1/29/16"	REV	D0-1	
	THIRD ANGLE PROJECTION	DRAWING NO.:	DC2.5-PE-C01	SHEET 1/1
	MM (INCH)	DO NOT SCALE DRAWING	SCALE 1:1	