


Overview

Product information



DGBSC-SG02/4-10080000436

Building wiring terminals, Rated current: 32A. Rated voltage (III/2) : 450V, max. 4 mm², Color: transparent, Contact surface : Tin

Product advantages

- Rotatable operating handle, easy to operate
- Suitable for all conductor types
- Suitable for field wiring, saving installation time

Product certification

Technical data

Product drawing

3D model

□

Connection capacity

Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4.0mm ²
AWG	24~12AWG
Strip length	12mm

Electrical parameters UL

Rated voltage (C)	600V
-------------------	------

Electrical parameters IEC

Rated voltage	450V
Rated current	32A
Rated current(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

Item properties

Connection method	Push-in spring connection
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Shell color	Transparent
Flammability rating	UL94V-2

Environmental data

Ambient temperature (operation)	-40°C~85°C
---------------------------------	------------

Accessories

Business data

Order number	10080000436
Packing unit	100
Minimum order quantity	
Products weight (without packaging)	3.22

