



*DC COMPONENTS CO., LTD.*

RECTIFIER SPECIALISTS

GBK6A  
THRU  
GBK6M

**TECHNICAL SPECIFICATIONS OF SINGLE-PHASE GLASS PASSIVATED BRIDGE RECTIFIER**

VOLTAGE RANGE - 50 to 1000 Volts

CURRENT - 6.0 Amperes

**FEATURES**



- \* Ideal for printed circuit board
- \* Surge overload rating: 150 Amperes peak
- \* Glass passivated junction

**MECHANICAL DATA**

- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Terminals: MIL-STD-202E, Method 208 guaranteed
- \* Polarity: Symbols molded or marked on body
- \* Mounting position: Any

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



	SYMBOL	GBK6A	GBK6B	GBK6D	GBK6G	GBK6J	GBK6K	GBK6M	UNITS
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	Volts
Maximum RMS Bridge Input Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current @T <sub>c</sub> =100°C (with heatsink Note 2) (without heatsink)	I <sub>(AV)</sub>	6.0 3.3							Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	150							Amps
Maximum Forward Voltage Drop per element at 3.0A DC	V <sub>F</sub>	1.1							Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage per element	I <sub>R</sub>	@T <sub>J</sub> = 25°C 10							μAmps
		@T <sub>J</sub> = 125°C 500							
I <sup>2</sup> t Rating for Fusing (t<8.3ms)	I <sup>2</sup> t	120							A <sup>2</sup> Sec
Typical Junction Capacitance ( Note1)	C <sub>J</sub>	55							pF
Typical Thermal Resistance (Note 2)	R <sub>θJC</sub>	1.8							°C/W
Operating Temperature Range	T <sub>J</sub>	-55 to +150							°C
Storage Temperature Range	T <sub>STG</sub>	-55 to +150							°C

NOTES : 1.Measured at 1 MHz and applied reverse voltage of 4.0 volts

2.Thermal Resistance from Junction to Case per element Unit mounted on 100x100x1.6mm Cu plate heat-sink.

# RATING AND CHARACTERISTIC CURVES (GBK6A THRU GBK6M)

FIG. 1  
MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 2  
TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3  
TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4  
TYPICAL REVERSE CHARACTERISTICS





FIG. 5  
TYPICAL JUNCTION CAPACITANCE



DC COMPONENTS CO., LTD.