

Plug and socket specifications display

2/3/4/5/6/7 core specifications complete one station purchase



插头 (A)



插座 (E)



焊接芯件参数 Solder contact spec

DF12	2	3	4	5	6	7	DF16	2	3	4	5	6	7	8	9	10
公端绝缘体正面图 Male contact face view																
额定电流/电压 Rated current/voltage	5A-125V						7A-125V		6A-125V		5A-125V					
工作电压(AC.V)分钟 Operation limit voltage(AC.V.rms)	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200
耐电压(AC.V)分钟 Withstanding voltage(AC.V.rms)1 minute	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
绝缘阻抗(m Ω)DC500V Insulation resistance(m Ω)MIN.at DC 500V	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
接触阻抗(m Ω)DC1A Contact resistance(m Ω)MAX.at DC 1A	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5
接触体直径Φ (mm) Contact diameter	1.2	1.2	1.2	1.2	1.2	1.2	2.5	2.5	2.5	2	1.2	1.2	1.2	1.2	1.2	1.2

DF20	2	3	4	5	6	7	8	9	10	12	14	15
公端绝缘体正面图 Male contact face view												
额定电流/电压 Rated current/voltage	10A-250V			10A-150V		6A-150V		5A-150V				
工作电压(AC.V)分钟 Operation limit voltage(AC.V.rms)	250	250	250	200	200	200	200	200	200	200	200	200
耐电压(AC.V)分钟 Withstanding voltage(AC.V.rms)1 minute	1500	1500	1500	1000	1000	1000	1000	1000	1000	1000	1000	1000
绝缘阻抗(m Ω)DC500V Insulation resistance(m Ω)MIN.at DC 500V	1500	1500	1500	1000	1000	1000	1000	1000	1000	1000	1000	1000
接触阻抗(m Ω)DC1A Contact resistance(m Ω)MAX.at DC 1A	3	3	3	3	3	3	3	3	3	3	3	3
接触体直径Φ (mm) Contact diameter	3.0	3.0	3.0	3.0	2.0	2.0	1.5	1.5	1.5	1.5	1.5	1.5