

G (PF)

UL US cULus CE IP68 IP68 RoHS



技术参数

螺母规格: G (PF) 牙, 符合ISO与JIS平行螺纹管牙规范。
 产品材质: A,C,E,F部分采用UL认可尼龙PA66制成(防火等级UL94V-2), B及D部分采用标准EPDM户外耐候橡胶。(其他用途橡胶可接受定制)
 保护等级: IP68-10
 工作温度: 静态-40°C至100°C, 或瞬间可耐至120°C, 动态-20°C至20°C至80°C, 或瞬间可耐至100°C。
 产品特点: 精美型的外型设计, 特殊A型设计的夹紧圈与夹紧爪, 夹紧电缆范围大, 其电缆拉力特强, 气密性完美, 并可防水、防尘、抗盐、耐醇酸、油、油脂及一般溶剂。
 颜色种类: 黑色、灰色, 其它颜色可定做。

Thread: G (PF), Parallel Threads for Pipes-ISO and JIS
 Materials: UL approved Nylon PA66 (Flammability UL 94V-2) for A, C, E, F Parts; EPDM rubber for B, D parts
 Protection degree: IP68
 Working temperature: -40°C to 100°C
 Features: Exquisite and beautiful exterior design. The claws and seals of excellent design. Sealing nut have a "click" sound and re-open, can hold cable firmly and have a wider cable range. Resistant to salt water, weak acid, alcohol, oil, grease and common solvents
 Color: Black and gray (Special colors customizable)

夹紧圈形状 Seal Holes	螺母规格 Thread	规格 Sizes	适用电缆 Cable Range	螺纹外径 Thread O.D. (mm)	板孔孔径 Panel Mounting Hole	螺纹长度 Thread Length (mm)	扳手直径 Spanner Size (mm)	包装 Qty Pkg. pcs
A型	G (PF) 1/4	FGA13-05	5.5-3	13.157	13.2-13.4	9	19.18	50
	G (PF) 1/4	FGA13-06	7.0-4.5	13.157	13.2-13.4	9	19.18	50
	G (PF) 3/8	FGA11-06	7.0-4.5	16.862	16.7-16.9	10	22.22	50
	G (PF) 3/8	FGA11-07	10.6	16.862	16.7-16.9	10	22.22	50
	G (PF) 1/2	FGA21S-10	7-4	20.955	21-21.2	10	27.22	50
	G (PF) 1/2	FGA21S-11	10-6	20.955	21-21.2	10	27.22	50
	G (PF) 1/2	FGA21m-11	12-7	20.955	21-21.2	10	27.22	50
	G (PF) 3/4	FGA26S-14	14-9	26.411	26.5-26.8	12	33.27	50
	G (PF) 3/4	FGA26S-16	16-12	26.411	26.5-26.8	12.5	33.27	50
	G (PF) 1	FGA32S-16	18-14	33.249	33.3-33.6	12	42.33	50
	G (PF) 1 1/4	FGA32S-18	18-14	33.249	33.3-33.6	12	42.33	50
	G (PF) 1 1/2	FGA42S-25	25-21	41.91	42-42.3	15	53.62	10
B型	G (PF) 1/2	FGA48S-39	41-31	47.803	48-48.4	20	57.62	10
	G (PF) 3/4	FGA60-46	46-40	59.614	60-60.4	20	70.76	10
	G (PF) 3/4	FGA60-49	51-44	59.614	60-60.4	20	70.76	10
	G (PF) 3/4	FGA88-68	68-58	87.884	88-89	25	110.110	2
	G (PF) 3/4	FGA88-77	77-66	87.884	88-89	25	110.110	2
	G (PF) 1 1/4	FGB13-05	5.5-3	13.157	13.2-13.4	8	19.18	50
	G (PF) 1 1/4	FGB13-07	6.8-4	13.157	13.2-13.4	8	19.18	50
	G (PF) 3/8	FGB17-07	7-4	16.862	16.7-16.9	10	22.22	50
	G (PF) 3/8	FGB17-10	10.4-8.4	16.862	16.7-16.9	10	22.22	50
	G (PF) 1/2	FGB21-07	7-4	20.955	21-21.2	10	27.22	50
	G (PF) 1/2	FGB21-10	10.4-8.4	20.955	21-21.2	10	27.22	50
	A型	G (PF) 1/4	FGB26S-18	18-14	26.411	26.5-26.8	12	33.27
G (PF) 3/4		FGB32S-22	22-16	33.249	33.3-33.6	13.5	42.33	10
G (PF) 1		FGB32S-25	25-18	33.249	33.3-33.6	13.5	42.33	10
G (PF) 1 1/4		FGB42-25	25-18	41.91	42-42.3	15	53.62	10
G (PF) 1 1/4		FGB42-25	26.5-21	41.91	42-42.3	15	53.62	10
G (PF) 1 1/4		FGB42-25	32-24	41.91	42-42.3	15	53.62	10
NPT 3/8		NPA17-06	7-4	17.055	17-17.5	13	22	50
NPT 3/8		NPA17-10	10-6	17.055	17-17.5	13	22	50
NPT 1/2		NPA21-10	11-7	21.223	21-22.3	13	27	50
NPT 3/4		NPA26-16	14-9	21.223	21-22.3	13	27	50
NPT 3/4		NPA26-18	16-12	26.568	26.568	15	33	50
NPT 1		NPA32-22	18-14	26.568	26.568	15	33	50
B型	NPT 1 1/2	NPA32-25	25-18	33.227	33-33.6	17	42	10
	NPT 3/8	NPB17-07	7-4	17.055	17-17.5	15	22	50
	NPT 3/8	NPB17-10	10.4-8.4	17.055	17-17.5	15	22	50
	NPT 1/2	NPB21-10	11-7	21.223	21-22.3	15	27	50
	NPT 3/4	NPB26-16	14-8.5	21.223	21-22.3	15	33	50
	NPT 3/4	NPB26-18	16-12	26.568	26.568	15	33	50
	NPT 1	NPB32-22	18-14	26.568	26.568	15	33	50
	NPT 1 1/2	NPB32-25	22-16	33.227	33-33.6	17	42	10
	NPT 1 1/2	NPB32-25	25-18	33.227	33-33.6	17	42	10
	NPT 1 1/4	NPB42-25	26.5-21	41.984	41.984	17	52	10
	NPT 1 1/4	NPB42-25	32-24	41.984	41.984	17	52	10

cULus cULus CE IP68 IP68 RoHS



技术参数

螺母规格: 公制牙 (Metric), PG牙及G (PF) 牙
 产品材质: A,C,F部分采用特殊UL认可之尼龙制成, B及D部分采用标准EPDM户外耐候橡胶。(其他用途橡胶可接受定制)
 保护等级: IP68-10
 工作温度: 静态-40°C至100°C, 或瞬间可耐至120°C, 动态-20°C至90°C, 或瞬间可耐至100°C。
 产品特点: 特殊A型设计的夹紧圈与夹紧爪, 夹紧电缆范围大, 其电缆拉力特强, 气密性完美, 并可防水、防尘、抗盐、耐醇酸、酒精、油、油脂及一般溶剂。
 颜色种类: 黑色、灰色, 其它颜色可定做。

Thread: Metric, PG and G (PF)
 Materials: UL approved Nylon PA66 (Flammability UL 94V-2) for A, C, F Parts; EPDM rubber for B, D parts
 Protection degree: IP68-10
 Working temperature: -40°C to 100°C
 Features: The claws and seals of excellent design. Sealing nut have a "click" sound and re-open, can hold cable firmly and have a wider cable range. Resistant to salt water, weak acid, alcohol, oil, grease and common solvents
 Color: Black and gray (Special colors customizable)

夹紧圈形状 Seal Holes	螺母规格 Thread	规格 Sizes	适用电缆 Cable Range	螺纹外径 Thread O.D. (mm)	板孔孔径 Panel Mounting Hole	螺纹长度 Thread Length (mm)	扳手直径 Spanner Size (mm)	包装 Qty Pkg. pcs
A型	M12x1.5	MGB12-P-05-ST	5.5-3	12	12-12.3	8.5	18.15	10
	M12x1.5	MGB12-P-07-ST	6.8-4	12	12-12.3	8.5	18.15	10
	M16x1.5	MGB16-P-07-ST	7-4	16	16-16.3	10	22.22	10
	M16x1.5	MGB16-P-10-ST	10-6.4	16	16-16.3	10	22.22	10
	M20x1.5	MGB20-P-13-ST	13-8	20	20-20.3	11.7	27.77	10
	M25x1.5	MGB25-P-18-ST	15.8-12	25	25-25.4	10	33.33	10
	M12x1.5	MGB12L-P-05	5.5-3	12	12-12.3	15	18.19	10
	M12x1.5	MGB12L-P-08	8-4	12	12-12.3	15	18.19	10
	M16x1.5	MGB16L-P-07	7-4	16	16-16.3	15	22.22	10
	M16x1.5	MGB16L-P-10	10-6.4	16	16-16.3	15	22.22	10
	M20x1.5	MGB20L-P-11	11.5-8	20	20-20.3	15	27.77	10
	M25x1.5	MGB25L-P-15	13.8-8	25	25-25.4	15	33.33	10
B型	PG 7	PGB7-P-05	5.5-3	12.5	12.5-12.8	8	17.15	10
	PG 7	PGB7-P-07	6.8-4	12.5	12.5-12.8	8	17.15	10
	PG 9	PGB9-P-05	5.5-3	15.2	15-15.5	8.5	22.19	10
	PG 9	PGB9-P-09	8-4	15.2	15-15.5	8.5	22.19	10
	PG 11	PGB11-P-07	7-4	18.6	18.6-18.9	9	24.22	10
	PG 11	PGB11-P-10	10-6.4	18.6	18.6-18.9	9	24.22	10
	PG 13.5	PGB13.5-P-08	8.8-5	20.4	20.4-20.7	10	27.74	10
	PG 13.5	PGB13.5-P-11	11.5-6	20.4	20.4-20.7	10	27.74	10
	PG 16	PGB16-P-10	11-7	22.5	22.5-22.8	10	30.77	10
	PG 16	PGB16-P-13	13-8	22.5	22.5-22.8	10	30.77	10
	PG 21	PGB21-P-16	15.8-12	28.3	28.3-28.7	12	38.33	10
	A型	G (PF) 1/4	FGP11/4	5.5-3	13.157	13.2-13.4	8	19.19
G (PF) 1/4		FGP13/8	6.8-4	13.157	13.2-13.4	8	19.19	10
G (PF) 3/8		FGP17-07	7-4	16.662	16.7-16.9	10	22.22	10
G (PF) 3/8		FGP17-10	10-6.4	16.662	16.7-16.9	10	22.22	10
G (PF) 1/2		FGP21S-07	7-4	20.955	21-21.2	10	27.22	10
G (PF) 1/2		FGP21S-08	8.8-5	20.955	21-21.2	10	27.22	10
G (PF) 3/4		FGP21S-10	10-6.4	20.955	21-21.2	10	27.22	10
G (PF) 3/4		FGP21S-11	11-7	20.955	21-21.2	10	27.22	10
G (PF) 1		FGP21M-07	7-4	20.955	21-21.2	12	27.74	10
G (PF) 1		FGP21M-08	8.8-5	20.955	21-21.2	12	27.74	10
G (PF) 1 1/4		FGP21M-11	11.5-6	20.955	21-21.2	12	27.74	10
B型		G (PF) 1/4	FGP11/4	5.5-3	13.157	13.2-13.4	8	19.19
	G (PF) 1/4	FGP13/8	6.8-4	13.157	13.2-13.4	8	19.19	10
	G (PF) 3/8	FGP17-07	7-4	16.662	16.7-16.9	10	22.22	10
	G (PF) 3/8	FGP17-10	10-6.4	16.662	16.7-16.9	10	22.22	10
	G (PF) 1/2	FGP21S-07	7-4	20.955	21-21.2	10	27.22	10
	G (PF) 1/2	FGP21S-08	8.8-5	20.955	21-21.2	10	27.22	10
	G (PF) 3/4	FGP21S-10	10-6.4	20.955	21-21.2	10	27.22	10
	G (PF) 3/4	FGP21S-11	11-7	20.955	21-21.2	10	27.22	10
	G (PF) 1	FGP21M-07	7-4	20.955	21-21.2	12	27.74	10
	G (PF) 1	FGP21M-08	8.8-5	20.955	21-21.2	12	27.74	10
	G (PF) 1 1/4	FGP21M-11	11.5-6	20.955	21-21.2	12	27.74	10