

## Vinyl-insulated Ring Terminals

Cable size: 1.5 ~ 2.5mm<sup>2</sup> (A.W.G.16 ~ 14) Max current: I<sub>max</sub>=27A Temperature: 75°C

Material: Purple copper Sheath: PVC Thickness: 0.8mm

ITEM NO	USA screw	Screw dia. d2 (mm)	Dimension (mm)					Color
			B	L	F	H	Dφ	
RV 2-3	#4	3.2	6.6	17.8	4.3	10.0	4.9	blue
RV 2-3.5 S	#6	3.7	6.6	17.8	4.3			
RV 2-3.5 M	#6	3.7	6.6	20.0	6.5			
RV 2-3.5 L	#6	3.7	8.5	22.5	7.75			
RV 2-4 S	#8	4.3	6.6	20.0	6.5			
RV 2-4 L	#8	4.3	8.5	22.5	7.75			
RV 2-5 S	#10	5.3	8.5	22.5	7.75			
RV 2-5 L	#10	5.3	9.5	22.5	7.25			
RV 2-6	1/4	6.4	12.0	27.6	11.0			
RV 2-8	5/16	8.4	12.0	27.6	11.0			
RV 2-10	3/8	10.5	14.6	31.2	13.9			
RV 2-12	1/2	13.0	19.2	36.5	16.5			

