


NOTE:

- * Zinc alloy die cast housing and cylinder, Bright nickel plated standard.
- * 4 disc tumbler mechanism, Brass keys, nickel plated.
- * Golden plated contacts and terminals.
- * All keyed alike.
- * "12" position (8-1, 4-5 ON), "3" position (1-3, 5-7 ON).
- * Key no: A126;

SPECIFICATION:

- * UL approval standard.
- * Contact Rating: 4A 125VAC, 2A 250VAC.
- * Contact Resistance: 50 Milli-Ohms Max.
- * Insulation Resistance: 500 Meg-Ohms Min. (500VDC)
- * Dielectric Strength: 1500 VAC-1 Minute.

DESCRIPTION	SWITCH LOCK			
PART NO.	S20110-2-6			
MATERIAL	ZDC2			
NOTE				
APPROVED BY	CHECKED BY	DRAWN BY		楊光雲
TOLERANCES	⊕	UNIT	mm	SCALE 1:1
>0 ±0.3				
>6 ±0.5				
>30 ±0.8				
>120 ±1.2				
>315 ±1.6				
>1000 ±2				
 興瀚企業股份有限公司 Salecom. Electronics Co., Ltd.				
REV. A	WT. g	DATE	19.06.11	

△	REV. NO.	COORDINATES	WAS	NEW	DATE	BY
1	2	3	4	5	6	7