

Copper Tube Terminals

Material: Purple copper

ITEM NO	Screw dia.d2(mm)	Dimension(mm)							Cable size(mm ²)
		dφ	Dφ	B	L1	L	t1	t	
SC 1.5-5	5.3	1.9	3.35	8.0	6.5	18.0	1.0	0.7	1.5
SC 2.5-4	4.3	2.6	4.0	8.0	7.0	18.0	1.0	0.7	2.5
SC 2.5-5	5.3	2.6	4.0	8.0	7.0	20.0	1.0	0.7	2.5
SC 4-5	5.3	3.4	5.0	9.0	7.5	20.0	1.0	0.7	4
SC 4-6	6.4	3.4	5.0	10.0	7.5	20.0	1.0	0.7	4
SC 6-5	5.3	4.1	5.5	10.0	8.8	26.0	1.1	0.7	6
SC 6-6	6.4	4.1	5.5	11.0	8.8	26.0	1.0	0.7	6
SC 6-8	8.4	4.1	5.5	12.0	8.8	27.0	0.8	0.7	6
SC 10-5	5.3	5.2	7.0	11.5	9.5	26.5	1.5	0.9	10
SC 10-6	6.4	5.2	7.0	11.8	9.5	26.5	1.5	0.9	10
SC 10-8	8.4	5.2	7.0	12.8	9.5	26.5	1.3	0.9	10
SC 16-6	6.4	6.0	8.0	12.0	11.5	32.4	1.65	1.0	16
SC 16-8	8.4	6.0	8.0	13.3	11.5	32.4	1.6	1.0	16
SC 16-10	10.5	6.0	8.0	15.0	11.5	32.4	1.4	1.0	16
SC 25-6	6.4	7.5	9.5	14.0	12.0	34.0	2.0	1.0	25
SC 25-8	8.4	7.5	9.5	14.0	12.0	34.0	2.0	1.0	25
SC 25-10	10.5	7.5	9.5	15.7	12.0	34.0	1.7	1.0	25
SC 35-6	6.4	8.4	11.0	16.0	13.5	36.0	2.5	1.3	35
SC 35-8	8.4	8.4	11.0	16.0	13.5	36.0	2.5	1.3	35
SC 35-10	10.5	8.4	11.0	16.0	13.5	37.0	2.5	1.3	35
SC 50-6	6.4	9.6	12.5	18.0	16.0	42.5	2.9	1.45	50
SC 50-8	8.4	9.6	12.5	18.0	16.0	42.5	2.9	1.45	50
SC 50-10	10.5	9.6	12.5	18.0	16.0	42.5	2.9	1.45	50
SC 50-12	12.5	9.6	12.5	18.0	16.0	43.0	2.9	1.45	50
SC 70-6	6.4	12.0	15.0	22.0	19.5	51.0	3.0	1.5	70
SC 70-8	8.4	12.0	15.0	22.0	19.5	51.0	3.0	1.5	70
SC 70-10	10.5	12.0	15.0	22.0	19.5	51.0	3.0	1.5	70
SC 70-12	13.0	12.0	15.0	22.0	19.5	51.0	3.0	1.5	70
SC 95-8	8.4	13.6	17.2	24.6	20.0	57.0	3.6	1.8	95
SC 95-10	10.5	13.6	17.2	24.6	20.0	57.0	3.6	1.8	95
SC 95-12	13.0	13.6	17.2	24.6	20.0	57.0	3.6	1.8	95
SC 95-14	15.0	13.6	17.2	24.6	20.0	57.0	3.6	1.8	95
SC 120-10	10.5	16.0	20.0	28.8	23.0	63.0	4.0	2.0	120
SC 120-12	13.0	16.0	20.0	28.8	23.0	63.0	4.0	2.0	120
SC 120-14	15.0	16.0	20.0	28.8	23.0	63.0	4.0	2.0	120
SC 150-10	11.0	16.8	21.0	30.0	24.5	70.0	4.1	2.1	150
SC 150-12	13.0	16.8	21.0	30.0	24.5	70.0	4.1	2.1	150
SC 150-14	15.0	16.8	21.0	30.0	24.5	70.0	4.1	2.1	150
SC 150-16	17.0	16.8	21.0	30.0	24.5	70.0	4.1	2.1	150
SC 185-10	11.0	18.7	23.7	34.5	30.5	79.0	5.0	2.5	185
SC 185-12	13.0	18.7	23.7	34.5	30.5	79.0	5.0	2.5	185
SC 185-14	15.0	18.7	23.7	34.5	30.5	79.0	5.0	2.5	185
SC 185-16	17.0	18.7	23.7	34.5	30.5	79.0	5.0	2.5	185
SC 240-12	13.0	21.0	26.0	37.5	35.0	91.0	5.0	2.5	240
SC 240-14	15.0	21.0	26.0	37.5	35.0	91.0	5.0	2.5	240
SC 240-16	17.0	21.0	26.0	37.5	35.0	91.0	5.0	2.5	240
SC 240-18	19.0	21.0	26.0	37.5	35.0	91.0	5.0	2.5	240
SC 300-16	17.0	23.7	30.7	43.0	44.0	103.0	7.0	3.5	300
SC 300-20	21.0	23.7	30.7	43.0	44.0	103.0	7.0	3.5	300
SC 400-16	17.0	27.0	34.0		46.0	113.0			400
SC 400-20	21.0	27.0	34.0		46.0	113.0			400
SC 500-16	17.0	30.0	38.0		50.0	123.0			500
SC 500-20	21.0	30.0	38.0		50.0	123.0			500
SC 630-20	21.0	35.0	45.0		56.0	135.0			630
SC 800-BL	-	39.0	50.0		60.0	170.0			800
SC 1000-BL	-	44.0	56.0		87.0	200.0			1000

