

SKEF 35



$V_{RSM}^* V_{RRM}$ V	V_{VRMS} V	$I_D = 35 \text{ A } (T_c = 29^\circ \text{C})$ Types	C_{max} μF	R_{min} Ω
400	125	SKEF 35/04		0,3
800	250	SKEF 35/08		0,7
1200	400	SKEF 35/12		1
1600	500	SKEF 35/16		1,5

Power Bridge Rectifiers Dual 1/2 Bridge Power Rectifiers

SKEF 35

Features

- Square plastic case with isolated metal base plate and fast-on connectors
- Blocking voltage up to 1600 V
- High surge current
- Easy chassis mounting
- UL recognized plastic material


Typical Applications


- Rectifier for power supplies
- Input rectifier for variable frequency drives
- Rectifier for DC motor field supplies
- Battery charger rectifiers
- Recommended snubber network:
RC: 50 Ω , 0.1 μF ($P_R = 1 \text{ W}$)

1) Freely suspended or mounted on an insulator

2) Mounted on a painted metal sheet of min. 250 x 250 x 1 mm

Symbol	Conditions	Values	Units
I_D	$T_a = 45^\circ \text{C}$, P1/120 black $T_a = 40^\circ \text{C}$, chassis ²⁾	22 13,5	A A
I_{DCL}	$T_a = 45^\circ \text{C}$, P1/120 black $T_a = 40^\circ \text{C}$, chassis ²⁾ $T_a = 45^\circ \text{C}$, isolated ¹⁾	18,5 12 3,9	A A A
I_{FSM}	$T_{vj} = 25^\circ \text{C}$, 10 ms $T_{vj} = 150^\circ \text{C}$, 10 ms	380 330	A A
i^2t	$T_{vj} = 25^\circ \text{C}$, 8,3 ... 10 ms $T_{vj} = 150^\circ \text{C}$, 8,3 ... 10 ms	700 540	A^2s A^2s
V_F	$T_{vj} = 25^\circ \text{C}$, $I_F = 150 \text{ A}$	max. 1,9	V
$V_{(TO)}$	$T_{vj} = 150^\circ \text{C}$	max. 0,85	V
r_T	$T_{vj} = 150^\circ \text{C}$	max. 7	m Ω
I_{RD}	$T_{vj} = 25^\circ \text{C}$, $V_{RD} = V_{RRM}$ $T_{vj} = 150^\circ \text{C}$, $V_{RD} = V_{RRM} \geq V$	300	μA μA
I_{RD}	$T_{vj} = 150^\circ \text{C}$, $V_{RD} = V_{RRM}$ $T_{vj} = 25^\circ \text{C}$, $V_{RD} = V_{RRM} \geq V$	5	μA μA
t_{rr}	$T_{vj} = 25^\circ \text{C}$	10	μs
f_G		2000	Hz
$R_{th(j-a)}$	isolated ¹⁾ chassis ²⁾	14,5 4,2	K/W K/W
$R_{th(j-c)}$	total	1,5	K/W
$R_{th(c-s)}$	total	0,15	K/W
T_{vj}		- 40 ... + 150	$^\circ\text{C}$
T_{stg}		- 55 ... + 150	$^\circ\text{C}$
V_{isol}	a.c. 50 ... 60 Hz; r.m.s.; 1 s / 1 min. to heatsink	3000 / 2500 2 \pm 15 %	V- Nm Nm m/s ²
M_s			
M_t			
a			
w	approx.	18	g
F_u		25	A
Case		G 10b	





Case G 10b

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.