



8050S

NPN SILICON TRANSISTOR


LOW VOLTAGE HIGH
CURRENT SMALL SIGNAL
NPN TRANSISTOR

DESCRIPTION

The UTC **8050S** is a low voltage high current small signal NPN transistor, designed for Class B push-pull audio amplifier and general purpose applications.

FEATURES

- *Collector current up to 700mA
- *Collector-Emitter voltage up to 20V
- *Complementary to UTC 8550S




ORDERING INFORMATION

Ordering Number			Package	Pin Assignment			Packing
Normal	Lead Free Plating	Halogen-Free		1	2	3	
8050S-x-AE3-R	8050SL-x-AE3-R	8050SG-x-AE3-R	SOT-23	E	B	C	Tape Reel
8050S-x-T92-B	8050SL-x-T92-B	8050SG-x-T92-B	TO-92	E	C	B	Tape Box
8050S-x-T92-K	8050SL-x-T92-K	8050SG-x-T92-K	TO-92	E	C	B	Bulk

<p>8050SL-x-AE3-R</p>	<p>(1) B: Tape Box, K: Bulk, R: Tape Reel</p> <p>(2) AE3: SOT-23, T92: TO-92</p> <p>(3) x: refer to Classification of h_{FE2}</p> <p>(4) G: Halogen Free, L: Lead Free, Blank: Pb/Sn</p>
-----------------------	---

MARKING (For SOT-23 Package)



■ ABSOLUTE MAXIMUM RATING (Ta=25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V_{CBO}	30	V
Collector-Emitter Voltage		V_{CEO}	20	V
Emitter-Base Voltage		V_{EBO}	5	V
Collector Current		I_C	700	mA
Collector Dissipation(Ta=25°C)	SOT-23	P_C	350	mW
	TO-92		1	W
Junction Temperature		T_J	+150	°C
Storage Temperature		T_{STG}	-40 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (Ta=25°C, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	BV_{CBO}	$I_C = 100\mu A, I_E = 0$	30			V
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C = 1mA, I_B = 0$	20			V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_E = 100\mu A, I_C = 0$	5			V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = 30V, I_E = 0$			1	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB} = 5V, I_C = 0$			100	nA
DC Current Gain(note)	h_{FE1}	$V_{CE} = 1V, I_C = 1mA$	100		400	
	h_{FE2}	$V_{CE} = 1V, I_C = 150mA$	120			
	h_{FE3}	$V_{CE} = 1V, I_C = 500mA$	40			
Collector-Emitter Saturation Voltage	$V_{CEO(SAT)}$	$I_C = 500mA, I_B = 50mA$			0.5	V
Base-Emitter Saturation Voltage	$V_{BEO(SAT)}$	$I_C = 500mA, I_B = 50mA$			1.2	V
Base-Emitter Saturation Voltage	$V_{BEO(SAT)}$	$V_{CE} = 1V, I_C = 10mA$			1.0	V
Current Gain Bandwidth Product	f_T	$V_{CE} = 10V, I_C = 50mA$	100			MHz
Output Capacitance	Cob	$V_{CB} = 10V, I_E = 0, f = 1MHz$		9.0		pF

■ CLASSIFICATION OF h_{FE2}


RANK	C	D	E
RANGE	120-200	160-300	280-400

■ TYPICAL CHARACTERISTICS


Static Characteristics




DC Current Gain




Base-Emitter on Voltage




Saturation Voltage



Current Gain-Bandwidth Product



Collector Output Capacitance



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.