


A-A Sec



B-B Sec

■ SPECIFICATIONS

- Voltage Rating : 300V AC/DC
- Current Rating : 6A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000M $\Omega$  min.
- Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m $\Omega$  max.

■ TERMINAL

- Applicable Wires : AWG # 20-26
- Material : Brass
- Finish : Tin Plated
- Thickness : 0.2 mm
- Q' ty : 7,000 pcs./Reel

SHALLIN ELECTRONICS CO., LTD.		APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
		林陳鏞	1:1	mm	.0	$\pm 0.3$	ECR	RoHS compliant	06/04/01			
PART NO		CHECKED BY	PROJ	VER NO.	.00	$\pm 0.2$	ECR	200608-003	06/08/10	CUSTOMER		
		YY10CT			.000	$\pm 0.1$	ECR	200706-003	07/06/04			
Y1.3mm Power Connectors Terminal		DRAWN BY	DATE	SIZE	ALL	$\pm$				Conforms to The RoHS Instruction		
		黃科源	2007/06/04	A4	ANGLE	0 $^{\circ}$	$\pm$					
					0 $^{\circ}$	$\pm$						