



### EUROCEL ALUMINIUM FOIL TAPE

#### Short description:

Nominal dead soft aluminum foil with aggressive solvent acrylic adhesive and protected by easy release liner.

#### Product Data

<b>Backing:</b>	0.030 mm BOPP film
<b>Adhesive:</b>	Acrylic adhesive
<b>Total thickness</b>	0.050 mm
<b>Adhesion to steel</b>	18 N/25mm
<b>Tensile strength MD</b>	37.5 N/25mm
<b>Elongation at break</b>	3.0 %
<b>Temp. Resistance</b>	100 °C ( For short period )

#### Application

Super performance, professional grade 30u foil tape. Ideal for sealing joints/seams against moisture and vapor on foil jacketing insulation. Suitable for many other permanent sealing, holding, splicing or masking applications requiring the protection offered by a foil backing.

Features	Benefits
Excellent Peel Adhesion	<ul style="list-style-type: none"><li>➤ Good initial tack</li><li>➤ Permanent bonding</li></ul>
Good Water and Fire Resistance	<ul style="list-style-type: none"><li>➤ Outstanding temperature</li><li>➤ Aging resistance</li></ul>

*Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.*

SICAD S.A., 20 Cocopan Crescent, Driehoek, Germiston – South Africa  
Tel.+27 11 776 8200; Fax +27 11 873 2396 export market; Fax +39 02 96780832 domestic market;  
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss