

> Ultra Fast Chargers

Offer the ultimate in speed charging. In as little as one hour one can use the same batteries again, saving time and money.

Camelion.

BC-0907

Charges:

1-4 x  **AA**
1-4 x  **AAA**

Ni-MH



AC Adapter



Car Adapter

SPECIFICATIONS

AC To DC Adapter

Input Voltage: AC 100 ~ 240V 50/60 Hz

Output Voltage: 12V DC

Car Plug

Output Voltage: 12V DC

Charger

Charging Currents

12V DC Input

4x(1.4V = 2200 mA) AA Size

4x(1.4V = 800 mA) AAA Size

MAIN FEATURES

- **4 Independent Charging Channels**
- **6 Level Charge Protection**
 - - dv Cut-Off
 - Timer Control Protection (1.5 hours)
 - Over Temperature Protection
 - Reverse Polarity Protection
 - Over Current and Short Circuit Protection
 - Defective and Non-rechargeable Battery Detection
- **Low Current Leakage** Minimizes loss of capacity and maintains battery charge by controlling current leakage.
- **Trickle Charge** maintains battery charge.
- **World Voltage Switch Adapter**
- **Battery Refresh** reduces memory effect and enables full discharge for long battery life.
- **Car Plug Adapter**
- **Pulse Charging Technology** for fast, efficient charging.
- **Easy To Read LCD Display** shows Charging Progress, Defective Battery, Battery Refresh Features.



CHARGING TIMES

Type of Battery	Charging Times (Appr.)
Ni-MH AA 2700 mAh	1.3 h
Ni-MH AA 2000 mAh	1.1 h
Ni-MH AA 1500 mAh	49 min
Ni-MH AAA800 mAh	1.2 h

AVAILABLE COLORS

 Silver

BARCODE



4 260033 157706

PACKAGING



Blister	
Plug:	TUV
Weight(g)	302
Dimensions (W) x (H) x (D) (mm)	125 x 205 x 67
Inner Carton	
Packs / Inner ctn	8
Net Weight(kg)	2.42
Gross Weight(kg)	2.7
Dimensions (L)x (W) x (H) (cm)	42 x 22 x 14
Outer Carton	
Packs / Carton	32
Net Weight(kg)	9.7
Gross Weight(kg)	11.3
Dimensions (L)x (W) x (H) (cm)	45.4 x 43.5 x 30
Volume(M ³)	0.0593