



**MEC PRODUCT SPECIFICATION**

**OPTOELECTRONICS COMPONENT**

**BL-B5334M Light Emitting Diode**

|                              |              |                 |
|------------------------------|--------------|-----------------|
| <b>MOBICON HOLDINGS LTD.</b> |              |                 |
| <b>Drawn</b>                 | <b>Sign.</b> | <b>Approved</b> |
| <b>Kandy Xu</b>              |              | <b>Leo Wong</b> |

**[www.mobicon.com](http://www.mobicon.com)**

## LED LAMPS SPECIFICATION

●COMMODITY : T-1 3/4 Standard 1.0"Lead, 5 $\phi$

PAGE : 2

●PART NUMBER : BL-B5334M

VERSION : 1.0

●ELECTRICAL AND OPTICAL CHARACTERISTICS ( Ta=25 °C )


| Chip          |                                   | Lens Appearance | Absolute Maximum Rating |         |         |             | Electro - optical Data(At 20mA) |      |               | Viewing Angle 2 $\theta$ 1/2 (deg) |
|---------------|-----------------------------------|-----------------|-------------------------|---------|---------|-------------|---------------------------------|------|---------------|------------------------------------|
| Emitted Color | Peak Wave Length $\lambda$ P (nm) |                 | $\Delta\lambda$ (nm)    | Pd (mW) | If (mA) | Peak If(mA) | Vf (V)                          |      | Iv Typ. (mcd) |                                    |
|               |                                   |                 |                         |         |         |             | Typ.                            | Max. |               |                                    |
| Bright Red    | 700                               | Water Clear     | 90                      | 40      | 15      | 50          | 2.2                             | 2.6  | 10.0          | 12                                 |

Remark : Viewing angle is the Off-axis angle at which the luminous intensity is half the axial luminous intensity.

●ABSOLUTE MAXIMUM RATINGS (Ta=25 °C )

Reverse Voltage ..... 5V  
 Reverse Current (-V<sub>R</sub> = 5V) ..... 100 $\mu$ A  
 Operating Temperature Range ..... -40 °C ~ 80 °C  
 Storage Temperature Range ..... -40 °C ~ 85 °C  
 Lead Soldering Temperature ..... 260 °C For 5 Seconds

●PACKAGE DIMENSIONS



NOTES : 1. All dimensions are in millimeters (inches).

2. Tolerance is  $\pm 0.5$ mm (0.01") unless otherwise specified.

3. Lead spacing is measured where the leads emerge from the package.

4. Specifications are subject to change without notice.

## LOW - CURRENT LED LAMPS(ROUND TYPES) SPECIFICATION







●COMMODITY : T-1 3/4 1.0"Lead 5 $\emptyset$  Led Lamp

PAGE : 3

●PART NUMBER : BL-B5334M

VERSION : 1.0

●ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25 °C)



## LED LAMPS SPECIFICATION

PAGE : 4

### RELIABILITY TEST

VERSION : 1.0

| Classification            | Test Item                                    | Reference Standard  | Test Conditions  | Result |
|---------------------------|--|---|--|--------|
| <b>Endurance Test</b>     | Operation Life                               | MIL-STD-750:1026<br>MIL-STD-883:1005<br>JIS C 7021 :B-1                     | Connect with a power<br>If=30mA<br>Ta=Under room temperature<br>Test time=1,000hrs | 0/100  |
|                           | High Temperature<br>High Humidity<br>Storage | MIL-STD-202:103B<br>JIS C 7021 :B-11  | Ta=85 °C ± 5 °C<br>RH=90% - 95%<br>Test time=1,000hrs                              | 0/100  |
|                           | High Temperature<br>Storage                  | MIL-STD-883:1008<br>JIS C 7021 :B-10  | High Ta=85 °C ± 5 °C<br>Test time=1,000hrs   | 0/100  |
|                           | Low Temperature<br>Storage                   | JIS-C-7021 :B-12  | Low Ta= -35 °C ± 5 °C<br>Test time=1,000hrs  | 0/100  |
| <b>Environmental Test</b> | Temperature<br>Cycling                       | MIL-STD-202:107D<br>MIL-STD-750:1051<br>MIL-STD-883:1010<br>JIS C 7021 :A-4 | -35 °C ~ 25 °C ~ 85 °C ~ 25 °C<br>30min 5min 30min 5min<br>Test Time=10 cycles     | 0/100  |
|                           | Thermal Shock                                | MIL-STD-202:107D<br>MIL-STD-750:1051<br>MIL-STD-883:1011                    | 85 °C ± 5 °C ~ -35 °C ± 5 °C<br>10min 10min<br>Test Time=10 cycles                 | 0/100  |
|                           | Solder Resistance                            | MIL-STD-202:201A<br>MIL-STD-750:2031<br>JIS C 7021 :A-1                     | T.sol=260 ± 5 °C<br>Dwell Time=10 ± 1sec.  | 0/50   |
|                           | Solderability                                | MIL-STD-202:208D<br>MIL-STD-750:2026<br>MIL-STD-883:2003<br>JIS C 7021 :A-2 | T.sol=230 ± 5 °C<br>Dwell Time=5 ± 1sec.   | 0/50   |
|                           | Lead Bending<br>Stress                       | MIL-STD-750:2036<br>JIS C 7021 :A-11  | 0° ~ 90° ~ 0° bend, 3 cycles<br>Weight 250g  | 0/50   |

### JUDGEMENT CRITERIA OF FAILURE FOR THE RELIABILITY

| Measuring Items    | Symbol         | Measuring conditions  | Judgement criteria for failure |
|--------------------|----------------|-----------------------|--------------------------------|
| Forward voltage    | V <sub>F</sub> | I <sub>F</sub> = 20mA | Over U <sub>x</sub> 1.2        |
| Reverse current    | I <sub>R</sub> | V <sub>R</sub> = 5V   | Over U <sub>x</sub> 2          |
| Luminous intensity | I <sub>V</sub> | I <sub>F</sub> = 20mA | Below S <sub>x</sub> 0.5       |

Note : 1. U means the upper limit of specified characteristics. S means initial value.

2. Measurement shall be taken between 2 hours and after the test pieces have been returned to normal ambient conditions after completion of each test.