



**PRESSURE ADAPTER**  
**Model : PS-403**

- \* 1 mV per kPa, psi, cm-Hg, in-Hg.
- \* Pressure : 0.5 to 500 psi.
- \* Vacuum : 0 to 29.99 in-Hg
- \* Port Connector : 1/4" NPT or 1/4" PS, included one adapter connector that convert the 1/4" NPT to 1/4" PS.
- \* Sensor material : Ceramic.
- \* Weight : 285 g.
- \* Meter Size : 100 x 50 x 25 mm.
- \* Pressure Sensor Size : 70 mm x 30 mm Dia.
- \* Cable length : Approx. 1 meter.
- \* Applications : Measure pneumatic pressures, measure automobile engine vacuum pressures, pressure for super heat measurements, hydraulic servo controls, refrigeration, air conditioning, food processing



**SOFT CARRYING CASE**  
**Model : CA-03, CA-06, CA-05A, CA-52A**

- CA-03 : Soft carrying case (190 x 90 x 55 mm)
- CA-04 : Soft carrying case (140 x 77 x 40 mm)
- CA-05A : Soft carrying case with sash (260 x 110 x 55 mm)
- CA-52A : Soft carrying case with sash (200 x 80 x 50 mm)



**ANEMOMETER ADAPTER**  
**Model : AM-402**

- \* Measurement : m/s, km/h, ft/min, knots.
- \* Output : 1 mV per 1 m/s, per 1 km/h, per 100 ft/min, per 1 knots.
- \* Size : 100x50x25 mm, Sensor-72 mm Dia.



**EMF ADAPTER**  
**Model : EMF-824**

- \* Electromagnetic field radiation adapter.
- \* Range : 20 micro Tesla, 200 milli-Gauss.
- \* 1 m Gauss (0.1 u Tesla) per 1 DC mV.
- \* Size : 100x50x25 mm.-main instrument.



CA-03 CA-04

CA-06  
CA-08



**HARD CARRYING CASE**

- CA-06 : Hard Carrying case. (280 x 195 x 65 mm)
- CA-08 : Hard Carrying case. (370 x 310 x 115 mm)



**SOUND ADAPTER**  
**Model : SL-406**

- \* Frequency and time weighting meet IEC 61672 class 2.
- \* A frequency weighting.
- \* Range : 3 ranges, 30 to 130 dB.
- \* Output : 1 mV per 1 dB.
- \* External Calibration adj. VR.



**LIGHT ADAPTER**  
**Model : LX-02**

- \* 3 ranges, 2,000/20,000/50,000 Lux
- \* Output : 0.1 mV per 1 Lux (range A).  
0.1 mV per 10 Lux (range B).  
0.1 mV per 100 Lux (range C).
- \* Size (main instrument) : 100x50x25 mm.

**HIGH VOLTAGE PROBE**

**Model : HV-40**

- \* DC : 0 to 40 KV, AC : 28 KV rms.
- \* 1000 M input impedance, 1/1000 att.
- \* DCV : ± 1% (1 to 20 KV), ± 1.5% (>20kV).
- \* ACV : ± 5% (>1 KV, 50/60Hz).
- \* Size : 340 x 30 x 30 mm.

