

SAFETY DATA SHEET

1. Identification

Product identifier	2-26® Multi-Purpose Precision Lubricant		
Other means of identification			
Product code	02004, 02005		
Recommended use	Multi-purpose lubricant		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplie	r/Distributor information		
Manufactured or sold by:			
Company name	CRC Industries, Inc.		
Address	885 Louis Dr. Warminster, PA 18974 US		
Telephone	045 074 4000		
General Information	215-674-4300		
Technical Assistance	800-521-3168		
Customer Service	800-272-4620		
24-Hour Emergency	800-424-9300 (US)		
(CHEMTREC)	703-527-3887 (International)		
Website	www.crcindustries.com		
2. Hazard(s) identification	n		
Physical hazards	Flammable aerosols	Category 1	
	Gases under pressure	Compressed gas	
Health hazards	Skin corrosion/irritation	Category 2	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
	Aspiration hazard	Category 1	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.		
Precautionary statement			
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Avoid breathing gas. Wash thoroughly after handling. Wear protective gloves.		
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing		

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

 Storage
 Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated light		64742-47-8	60 - 70
Light mineral oil		8042-47-5	10 - 20
n-Butyl stearate		123-95-5	3 - 5
Carbon dioxide		124-38-9	1 - 3
Petrolatum		8009-03-8	1 - 3
Sorbitan monooleate		68910-94-1	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Diarrhea. Irritation of eyes and mucous membranes. Irritation of nose and throat. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.	
General fire hazards	Extremely flammable aerosol.	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, please see the product label.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Light mineral oil (CAS 8042-47-5)	PEL	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
,	TWA	5000 ppm	
Light mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
n-Butyl stearate (CAS 123-95-5)	TWA	10 mg/m3	
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide	o Chemical Hazards		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Light mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
,	TWA	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
logical limit values	No biological exposure limits noted for	or the inaredient(s).	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.	
Individual protection measures,	such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection Hand protection	Wear protective gloves such as: Nitrile. Neoprene.	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.	
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance		
Physical state	Liquid.	
Form	Aerosol.	
Color	Amber.	
Odor	Mild petroleum.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	-72.4 °F (-58 °C) estimated	
Initial boiling point and boiling range	392 °F (200 °C) estimated	
Flash point	180 °F (82.2 °C) Tag Closed Cup	
Evaporation rate	Slow.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	0.6 % estimated	
Flammability limit - upper (%)	5.5 % estimated	
Vapor pressure	1558.1 hPa estimated	
Vapor density	> 1 (air = 1)	
Relative density	0.84 estimated	
Solubility (water)	Negligible.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	392 °F (200 °C) estimated	
Decomposition temperature	Not available.	
Viscosity (kinematic)	Not available.	
Percent volatile	88.4 % estimated	
10. Stability and reactivity		

	/	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.	
Chemical stability	Material is stable under normal conditions.	
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.	
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.	

11. Toxicological information

Information on likely routes of exposure Ingestion May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Symptoms of overexposure may be headache, dizziness, Inhalation tiredness, nausea and vomiting. Skin contact Causes skin irritation. Direct contact with eyes may cause temporary irritation. Eye contact Diarrhea. Irritation of nose and throat. Irritation of eyes and mucous membranes. May cause Symptoms related to the redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea physical, chemical and and vomiting. toxicological characteristics

Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Narcotic effects.

	- , · · · · · · · · · · · · · · · · · ·		
Product	Species	Test Results	
2-26® Multi-Purpose Precis	sion Lubricant		
Acute			
Dermal			
LD50	Rabbit	3006.2102 mg/kg estimated	
Inhalation			
LC50	Rat	58741.1172 ppm, 4 hours estimated	
Oral			
LD50	Rat	8565.0654 mg/kg estimated	
Subchronic			
Oral			
LD50	Rat	9380.1563 g/kg, 14 days estimated	

* Estimates for product may be based on additional component data not shown.

1 2				
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.			
Respiratory sensitization	Not available.			
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
IARC Monographs. Overall Evaluation of Carcinogenicity				
Light mineral oil (CAS 80	S 8042-47-5) 3 Not classifiable as to carcinogenicity to humans.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.			
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	May be fatal if swallowed and enters airways.			
Chronic effects	Prolonged inhalation may be harmful.			
12. Ecological information	1			

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results	
2-26® Multi-Purpose Precisi	on Lubricant			
Aquatic				
Acute				
Fish	LC50	Fish	9923.6641 ppm, 96 hours estimated	
Components		Species	Test Results	
Distillates (petroleum), hydro	treated light	(CAS 64742-47-8)		
Aquatic				
Acute				
Fish	LC50	Bluegill (Lepomis macrochirus)	2.2 mg/l, 96 hours	
baccumulative potential ability in soil her adverse effects	No data available. No data available. No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
. Disposal consideratio	ons			
sposal of waste from sidues / unused products	The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose in accordance with all applicable regulations.			
zardous waste code	Not regul	Not regulated.		
ntaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.			
. Transport informatior	ı			

DO	т	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable, Limited Quantity
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Special provisions	N82
	Packaging exceptions	306
	Packaging non bulk	None
	Packaging bulk	None
ΙΑΤ	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable, Limited Quantity
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo	Allowed.
	aircraft	
	Cargo aircraft only	Allowed.
IME)G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS, LIMITED QUANTITY

Transport hazard class(es)			
Class	2		
Subsidiary risk	-		
Packing group	Not applicable.		
Environmental hazards			
Marine pollutant	No.		
EmS	F-D, S-U		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
15. Regulatory information			
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication		
·	Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.		
TSCA Section 12(b) Export N	lotification (40 CFR 707, Subpt. D)		
Not regulated.			
SARA 304 Emergency releas	e notification		
Not regulated.			
US. OSHA Specifically Regu	lated Substances (29 CFR 1910.1001-1050)		
Not listed.	ection 313 - Toxic Chemical: Listed substance		
Not listed.	ection 313 - Toxic Chemical. Listed substance		
CERCLA Hazardous Substar	nce List (40 CFR 302.4)		
Not listed.			
CERCLA Hazardous Substar	nces: Reportable quantity		
Not listed.			
	Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.		
• •	112 Hazardous Air Pollutants (HAPs) List		
Not regulated.			
Clean Air Act (CAA) Section	112(r) Accidental Release Prevention (40 CFR 68.130)		
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
Food and Drug Administration (FDA)	Not regulated.		
	I Reauthorization Act of 1986 (SARA)		
Section 311/312	Immediate Hazard - Yes		
Hazard categories	Delayed Hazard - No		
	Fire Hazard - Yes Pressure Hazard - Yes		
	Reactivity Hazard - No		
SARA 302 Extremely	No		
hazardous substance			
US state regulations			
US. New Jersey Worker and	Community Right-to-Know Act		
Carbon dioxide (CAS 124			
	drotreated light (CAS 64742-47-8)		
US. Massachusetts RTK - Su			
Carbon dioxide (CAS 124 Light mineral oil (CAS 804			
	d Community Right-to-Know Law		
Carbon dioxide (CAS 124			
	drotreated light (CAS 64742-47-8)		
Light mineral oil (CAS 804	Light mineral oil (CAS 8042-47-5)		
US. Rhode Island RTK			
None.			

US. California Proposition 65

Consumer products

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s))	97.3 %
Consumer products (40 CFR 59, Subpt. C)	Not regulated

State

This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50 states.

VOC content (CA)	0 %
VOC content (OTC)	0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-12-2014	
Prepared by	Allison Cho	
Version #	01	
Further information	CRC # 591B/C	
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0 Personal protection: B	
NFPA ratings	Health: 2 Flammability: 3 Instability: 0	
Disclaimer	The information contained in this document applies to this specific material as supplied. It r be valid for this material if it is used in combination with any other materials. This informatic accurate to the best of CRC Industries' knowledge or obtained from sources believed by CI be accurate. Before using any product, read all warnings and directions on the label. For fu clarification of any information contained on this (M)SDS consult your supervisor, a health a professional, or CRC Industries.	