

### Brass - Open Barrel Terminals

#### Uninsulated Disconnect - Female



Type	Diagram	Wire size (mm <sup>2</sup> )	Dimensions		
			L	C	W
UDF		0.5 - 2	19	7.5	6.6
UDF2			16	6.4	3.2
UDF4			15.5	6.5	5
UDFC			19	7.4	6.8

All dimensions in mm. Subject to technical changes. "C" - with clip

#### Uninsulated Disconnect - Male



Type	Diagram	Wire size (mm <sup>2</sup> )	Dimensions		
			L	C	W
UDM		0.5 - 2	20	7.5	6.3

All dimensions in mm. Subject to technical changes.

#### Uninsulated Ring Lug



Type	Diagram	Wire size (mm <sup>2</sup> )	Dimensions		
			L	C	W
UR10		0.5 - 2	34	24	18.5
UR8			26	17.5	13.8
UR6			20.8	12.6	10
UR5			20.8	12.6	10
UR4			19.4	11.2	8.5
UR3			15.6	9.4	7

All dimensions in mm. Subject to technical changes.

#### Uninsulated Bullet - Female / Male



Type	Diagram	Wire size (mm <sup>2</sup> )	Dimensions		
			L	C	W
UULF4		0.5 - 2	17	6.7	3.95
UULM4		0.5 - 2.6	17.8	8.4	4

All dimensions in mm. Subject to technical changes.

#### Uninsulated Spade



Type	Diagram	Wire size (mm <sup>2</sup> )	Dimensions		
			L	C	W
US4		0.5 - 2	22	6.8	6.6

All dimensions in mm. Subject to technical changes.