

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

NOTES1:

- UL Standard
- 1.Rated Voltage/Current : 300V / 20A
- 2.Torque Value : M4, 10.53Lb.in
- 3.Wire Range : 12AWG

IEC Standard

- 1.Rated Voltage/Current : 750V / 57A
- 2.Torque Value : M4.0, 1.2N·m
- 3.Wire Range : 1.5~10mm²

NOTES2:


- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 15.00mm, Poles : N=02~12P
- 3.Stripping length : 8mm
- 4.Withstanding Voltage : AC3000V/1min.
- 5.Operating temperature: -40°C~+105°C
- 6.Undimensioned Tolerances:

Pitch range in mm	Nominal dimension range		Tolerance
	Over	Under	
6 TO 10	6 TO 10	5 TO 10	0.1/0
10 TO 24	10 TO 24	9 TO 24	0.15
±0.15	±0.20	±0.30	±0.50
±0.30	±0.70	±1.00	±1.30
±2°	±2°	±2°	±2°

7.RoHS Compliance

- DG15HSWP-1.2 - XXP - 1Y - 100A (H)
- (Series No.) (Poles) (Single Pitch) (Color): 1.(Grey) 2.(Blue) 3.(Black) 4.(Green) 5.(Orange) 6.(Red) 7.(Transparent) 8.(Yellow) 9.(White)
- 100A-(Standard) (RoHS)

DETACHED LISTS

PART NO.: /	NINGBO DEGSON ELECTRICAL CO., LTD
APPD: /	NAME: NINGBO DEGSON ELECTRICAL CO., LTD
CHKD: /	NAME: DG15HSWP-1.2-XXP-1Y-100A(H)
DRFT: /	TITLE: CUSTOMER DRAWING
	DRAWING NO.: /
THIRD ANGLE PROJECTION	DO NOT SCALE
	DRAWING SCALE
	1:1