



5.5mm/2.1mm DC to Type-C & Micro USB Adapter

Product Overview

03/24/2023

For the most up-to-date information, visit www.mouser.com or the supplier's website.

Description

DFRobot 5.5mm/2.1mm DC to Type-C and Micro USB Adapters feature a transmission voltage of $3V_{DC}$ to $28V_{DC}$ and PVC flame-retardant insulating material. These adapters utilize the in-line fixing method and operate within the 50°C to 56°C temperature range. The 5.5mm/2.1mm DC to Type-C and micro-USB adapters can power mobile phones, tablets, Raspberry Pi, and LattePanda devices



Features

- Female:
 - DC 5.5mm x 2.1mm
- Male:
 - Micro Type-C (FIT0784)
 - Micro USB (FIT0783)
- PVC flame-retardant insulating material
- In-line fixing method
- Black color

Specifications

- 3V_{DC} to 28V_{DC} transmission voltage range
- ≥10000 times plug service life
- 5.5mm x 2.1mm dimensions
- -50°C to 56°C operating temperature range





Specifications

- Mobile phones
- Tablets
- Raspberry Pi
- LattePanda devices

Mouser Part Numbers

View All Parts

To learn more, visit https://www.mouser.com/new/dfrobot/dfrobot-dc-female-adapters/