

# Torque, CO<sub>2</sub> Turbidity SERIES



## TORQUE METER, 15 Kg-cm

### Model : TQ-8800

- \* Professional torque meter with separate probe.
- \* 15 Kg-cm torque sensor included.
- \* 3 units : 15 Kg-cm/13 LB-inch/147.1 N-cm.
- \* Peak, Data hold, Zero, Max./ Min., Fast/Slow.
- \* RS232/USB computer interface.
- \* Size : 180 x 72 x 32 mm. RS-232.



## CO<sub>2</sub> METER, + Humidity, Temp. GCH-2018

- \* Function : CO<sub>2</sub> ( Carbon dioxide ) Humidity, Dew point, Temp..
- \* CO<sub>2</sub> range : 0 to 4,000 ppm.
- \* CO<sub>2</sub> resolution : 1 ppm.
- \* CO<sub>2</sub> sensor : NDIR, long term reliability.
- \* CO<sub>2</sub> repeatability : ± 20 ppm.
- \* CO<sub>2</sub> with alarm setting and warning.
- \* Humidity : 10 to 95 %RH, Temp. : 0 to 50 °C.
- \* Separate probe, easy operation.
- \* Record Max, Min value .
- \* RS232/USB computer interface.
- \* Power : 1.5 V battery ( UM-4/AAA ) x 6 PCs or DC 9V adapter in.

### GC-2028

- \* Same function as GCH-2018, but without humidity measurement.



## TURBIDITY METER

### Model : TU-2016

- \* Range : Auto range, two ranges, 0.00 to 50.00 NTU, 50 to 1,000 NTU.
- \* Resolution : 0.01 NTU/1 NTU.
- \* Accuracy : ± 5 % F.S. or ± 0.5 NTU, which ever is greater.
- \* Light source : LED, 850 nm.
- \* Record Max, Min value
- \* Power : 1.5 V battery ( UM-4/AAA ) x 6 PCs.
- \* 0 NTU and 100 NTU Calibration solution are included.
- \* Designed to meet ISO 7027.

## TORQUE WRENCH, 100 Kg-cm

### Model : TQ-8801

- \* Professional and Heavy duty torque wrench.
- \* Range : 100 Kg-cm, 980 Newton-cm.
- \* Unit : Kg-cm, LB-inch and Newton-cm.
- \* Peak value measurement.
- \* Data hold and peak hold.
- \* High/Low resolution selection.
- \* Fast/Slow sampling selection.
- \* Record Max. and Min. reading value.



## TORQUE WRENCH

### Model : TQ-8801

100.0 kg-cm  
FAST

RANGE: 10.0-100.0 Kg-cm  
98.1-981 N-cm  
9.8-98.6 lb-in

POWER HOLD SENSOR TYPE  
MAX./MIN. UNIT ZERO  
PEAK RESO. F/S

side view

- \* RS 232 computer interface.
- \* Microcomputer circuit, high performance.
- \* Die casting heavy duty & compact housing case.
- \* Complete set with the hard carrying case.
- \* Weight : 605 g ( 1.33 LB ).
- \* Size : 310 x 51 x 46 mm.