



Pitch range in mm			Nominal dimension range in mm					—
to 6	over 6 to 10	over 10 to 24	to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	⌒ ▭
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

文管中心  
 研发专用  
 2020.04.13  
 (仅限内部使用, 对外无效)

1	Pin header	Copper alloy	Sn Plated
ITEM	NAME OF PART	MATERIAL	NOTES
	额定电流/Rated Current(A)		15
	螺栓扭矩/Torque Tightening(N·m/Lb.in)		M4, 1.2/10.53
	线径范围/Wire Range(AWG)		18~14
	符合RoHS环保要求/Conform to RoHS		Yes

MATERIAL: /	SURFACE: /		
MAT NO.: /	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
STATUS: /			
APPD: Zhu WM 2020.04.13	NAME: K13-01Z(H)		
CHKD: Gao WG 2020.04.13	DRAWING NO.: K13-C02		
DRFT: Wu NK 2020.04.13	TYPE: CUSTOMER DRAWING		REV TO
⊕	SIZE: A4	SCALE: 5:1	SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE