

140 – 150
L/W

MASTER HIGH BAY

Generation 2



Range of high bays lights designed for illumination of interior premises in hangars, warehouses, cold storage facilities, production premises etc.

Ideal to use in any environment with heights 8m to 25m

PURE LIGHT

MASTER HIGH BAY SPECIFICATION



90 mm

58mm

470mm / 720 mm / 970mm / 1 220mm




Operating Voltage 170 ~264VAC
Overvoltage Protection 320V AC, 48h
Burst/Surge Protection 4kV
Power Factor > 0.97
CRI +70 / +80 optional
Colour temperature 4000K optional
Weight: 1.1kg, 1.7kg; 2,3kg; 3,5kg
Dimming optional. Range 1% to 100%
(DSI, DALI)


LED Code L80B10

Light Diagram


S - 29.0°




M - 61.0°



W - 87.0°



O - 63° + 20°



Product Code	Power	Colour Temp. K	Luminous Flux (Lm)	Product Code
Master 2	67W	5000K	10 200	M2-XK-Option
Master 3	99W	5000K	15 000	M3-XK-Option
Master 4	132W	5000K	20 150	M4-XK-Option
Master 5	162W	5000K	24 100	M5-XK-Option

Optional items

Code

Image

Side mount hanger bracket

CS00161-005-11

DALI2 driver

DALI2

D4i driver LMS Wireless

D4i

