


GuosaiA+國賽 Nylon-Fully Insulated Female Bullet Receptacles(Double Copper Sleeve)



尼龙全绝缘护套子弹形母插端子(加铜套)(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105°C
- 表面处理: 镀锡

Nylon-Fully Insulated Female Bullet Receptacles(Double Copper Sleeve)
(Apply in flexible wire)


- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105°C
- Plating: Tin

UL LISTED eUL CE SGS

FEMALE BULLET TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm ²)	最大电流 Max Current	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
				Wφ	bφ	Dφ	dφ	L	F	
FRFNY 0.5-078 D	24-18(0.3-1.0)	10A	0.3	3.5	2.0	3.9	1.4	25.0		透明白 white
FRFNY 1.25-156 D	22-16(0.5-1.5)	15A	0.4	5.9	3.9	4.2	1.7	24.5	14.0	红 red
FRFNY 2-156 D	16-14(1.5-2.5)	24A		5.9	3.9	4.2	2.4	24.5		蓝 blue

Nylon-Fully Insulated Male Bullet (Double Copper Sleeve)



尼龙全绝缘护套子弹形公插端子(加铜套)(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105°C
- 表面处理: 镀锡

Nylon-Fully Insulated Male Bullet (Double Copper Sleeve)
(Apply in flexible wire)

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105°C
- Plating: Tin

UL LISTED eUL CE SGS

MALE BULLET TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm ²)	最大电流 Max Current	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
				Wφ	bφ	Dφ	dφ	L	F	
MPFNY 0.5-078 D	24-18(0.3-1.0)	10A	0.3	5.5	2.0	3.6	1.4	26.6		透明白 white
MPFNY 1.25-156 D	22-16(0.5-1.5)	15A	0.4	7.5	4.0	4.2	1.7	25.5	15.5	红 red
MPFNY 2-156 D	16-14(1.5-2.5)	24A		7.5	4.0	4.2	2.4	25.5		蓝 blue