





PVC绝缘护套肩背形公母插端子(适用于软线)

- 材质: 黄铜
- 护套: PVC
- 表面处理: 镀锡

**Vinyl-Insulated Piggy Back Disconnect
(Apply in flexible wire)**

- Terminal Body: Brass
- Insulation: Vinyl
- Plating: Tin



尼龙全绝缘护套肩背形公母插端子(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

**Nylon-Fully Insulated Piggy Back Disconnect
(Apply in flexible wire)**

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin




PIGGY BACK TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm²)	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	W1	H	DΦ	dΦ	L	
PBDD 1.25-250	22-16(0.5-1.5)	10A	0.8×6.35	0.4×2	6.6	6.35	10.5	3.8	1.7	21.5	红 red
PBDD 2-250	16-14(1.5-2.5)	15A	0.8×6.35		6.6	6.35	10.5	4.3	2.3	21.5	蓝 blue
PBDD 5.5-250	12-10(4-6)	24A	0.8×6.35		6.6	6.35	13.0	5.5	3.4	24.5	黄 yellow

PIGGY BACK TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm²)	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	W1	H	DΦ	dΦ	L	
PBDFN 1.25-250	22-16(0.5-1.5)	10A	0.8×6.35	0.4×2	6.6	6.35	11.5	4.3	1.7	21.5	红 red
PBDFN 2-250	16-14(1.5-2.5)	15A	0.8×6.35		6.6	6.35	11.5	4.5	2.3	22.7	蓝 blue
PBDFN 5.5-250	12-10(4-6)	24A	0.8×6.35		6.6	6.35	14.0	6.6	3.4	24.5	黄 yellow

Nylon-Insulated Piggy Back Disconnect



尼龙绝缘护套肩背形公母插端子(适用于软线)


- 材质: 黄铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

**Nylon-Insulated Piggy Back Disconnect
(Apply in flexible wire)**

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin



Nylon-Insulated Piggy Back Disconnect(Double Copper Sleeve)



尼龙绝缘护套肩背形公母插端子(加铜套)(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

**Nylon-Insulated Piggy Back Disconnect(Double Copper Sleeve)
(Apply in flexible wire)**

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin



PIGGY BACK TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm²)	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	W1	H	DΦ	dΦ	L	
PBDDN 1.25-250	22-16(0.5-1.5)	10A	0.8×6.35	0.4×2	6.6	6.35	11.0	4.1	1.7	21.5	红 red
PBDDN 2-250	16-14(1.5-2.5)	15A	0.8×6.35		6.6	6.35	11.0	4.7	2.3	21.5	蓝 blue
PBDDN 5.5-250	12-10(4-6)	24A	0.8×6.35		6.6	6.35	14.0	6.6	3.4	24.5	黄 yellow

PIGGY BACK TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm²)	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	W1	H	DΦ	dΦ	L	
PBDDN 1.25-250 D	22-16(0.5-1.5)	10A	0.8×6.35	0.4×2	6.6	6.35	11.0	3.8	1.7	21.5	红 red
PBDDN 2-250 D	16-14(1.5-2.5)	15A	0.8×6.35		6.6	6.35	11.0	4.4	2.3	21.5	蓝 blue
PBDDN 5.5-250 D	12-10(4-6)	24A	0.8×6.35		6.6	6.35	14.0	5.7	3.4	24.5	黄 yellow