



2, 五金件: 表面电镀不可发黑/发麻。
 NOTES: 1, 弹簧上下活动灵活, 无卡住现象。

9	WASHER	$\varnothing 14.5 \times 8.2$	STEEL	Zn-PLATE	2	华司
8	WASHER	$\varnothing 16 \times 8.2$	STEEL	Zn-PLATE	2	华司
7	NUT	M7*0.75 ,t=2mm	STEEL	Zn-PLATE	2	螺母
6	PLASTIC	$\varnothing 4.7 \times 7.3$	PLASTIC	WHITE	1	塑胶粒
5	TERMINAL	$\varnothing 3.95$	STEEL	NICKEL-PLATE	1	端子
4	SPRING	$\varnothing 3.8$	STEEL	Zn-PLATE	1	弹簧
3	SCREW	M7*0.75 ,L=25mm	CUPRUM	YELLOW	1	螺杆
2	CONDUIT	$\varnothing 4.5$	CUPRUM	NICKEL-PLATE	1	导管
1	SHAFT		STEEL	NICKEL-PLATE	1	推杆
NO.	NAME	SPEC.	MATERIAL	PLATING	Q'TY	NOTE

		PROJ		SHEET 1 OF 1		
		单位 UNIT	MM	比例 SCALE	版本 REVISION	1.0
		制图 DRAWN BY		日期 DATE	2011 -3 -11	
日期 DATE	修订内容 DESCRIPTION	签章 SIGNATURE	设计 DESIGNED BY	图号 DRG. NO.		
			审核 APPROVED BY	料号 MODEL NO.		
			图名 DRG. DESCRIPTION	PIN SWITCH:P-6		