



### 4 channels THERMOMETER

#### Model : TM-946

- \* Type K/J, Pt 100 ohm, 4 display.
- \* 4 channels ( T1, T2, T3, T4 ), T1-T2, °C/°F.
- \* Display 4 channels Temp. at the same time.
- \* Type K : -100 to 1300 °C.
- \* Type J : -100 to 1200 °C.
- \* Pt 100 ohm : -199 to 850 °C.
- \* °C/°F, 0.1 degree/1 degree.
- \* Data hold, Record ( max., min. ).
- \* RS-232/USB computer interface, data logger.
- \* Optional Type K Temp. probe, refer page 47.
- \* Optional Pt-100 ohm Temp. probe, TP-101.
- \* DC 1.5V ( UM-4, AAA ) battery x 6 or DC 9V adapter in.



### THERMOMETER, Type K/J/R/E/T

#### Model : TM-9126

- \* Type K : -50 to 1300 °C, 0.1 °C/0.1 °F.
- Type J : -50 to 1150 °C, 0.1 °C/0.1 °F.
- Type T : -50 to 400 °C, 0.1 °C/0.1 °F.
- Type E : -50 to 900 °C, 0.1 °C/0.1 °F.
- Type R : 0 to 600 °C, 1 °C/1 °F.
- \* Professional thermometer with multi-function.
- \* Optional full range temperature probe.
- \* RS-232/USB computer interface.
- \* Data hold, Record ( Max., Min. ).
- \* DC 1.5V ( UM-4, AAA ) battery x 6 or DC 9V adapter in.

### Multi-function THERMOMETER, Real time data logger

#### Model : YK-2005TM

- \* High capacity, 16,000 data logger point.
- \* Real time data logger ( record year, month, date, hour, minute, second ).
- \* Multi-function : Type K, Type J, Pt100 ohm, Infrared Thermometer.
- \* Type K : -50 to 1300 °C, Type J : -100 to 1100 °C, Pt 100 ohm -200 to 850 °C.
- \* Optional probe : Type K probe, Type J probe,, PT 100 probe, IR probe.
- \* Max., Min., Data hold, zero adjust.
- \* RS-232/USB computer interface.
- \* Jumbo LCD display.
- \* DC 1.5V ( UM3, AA ) x 4 PCs or DC 9V adapter in.
- \* Size : 203 x 76 x 38 mm.



### THERMOMETER, all in 1

#### Model : PTM-818

- \* Cooperate with the type K Temp. probe.
- \* Range : -50 to 230 °C x 0.1 °C.
- \* Unit : °C, °F. internal adjustment.
- \* Meter with the probe, all in 1, easy operation.
- \* Hold function to freeze display value.
- \* Build in reverse display button.
- \* IP-67 Water resistance, heavy duty.
- \* DC 1.5V battery ( UM-4, AAA ) x 4.

### Separate probe, type K THERMOMETER

#### Model : PTM-806

- \* Cooperate with the type K Temp. probe.
- \* Range : -100 to 1300 °C x 0.1 °C.
- \* Unit : °C, °F. internal adjustment.
- \* Separate probe, easy for remoting measurement.
- \* Temp. probe, TP-01 is included.
- \* Optional temp. probe : TP-02A, TP-03, TP-04.
- \* Hold function to freeze display value.
- \* Build in reverse display button.
- \* DC 1.5V battery ( UM-4, AAA ) x 4.



### T1, T2, T1-T2, two displays

#### TWO CHANNEL THERMOMETER

#### Model : TM-925

- \* T1, T2, T1-T2, Type K/J.
- \* °C/°F, 0.1 degree/1 degree.
- \* Type K : -100 to 1300 °C.
- \* Type J : -100 to 1200 °C.
- \* Data hold, Record ( max., min. ).
- \* 1600 Data logger point.
- \* RS-232/USB interface, data logger.
- \* DC 9V battery ( 006P ) or DC 9V adapter in.