



LISTED 57RJ
CAT NO. 1920

NOTE

Except where indicated otherwise, the figures stated are test average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'.

**PROFESSIONAL GRADE
PVC INSULATION TAPE**
0.18mm x 18mm x 20m

GENERAL DESCRIPTION:

A professional grade PVC Electrical Insulation Tape that provides excellent electrical insulation with high adhesion, which can be applied over a wide temperature range. Once applied it provides high grade electrical insulation up to 600V within varying weather conditions.

- Flame retardant
- Insulation up to 600 Volt
- UL listed 57RJ
- PolyVinyl Chloride (PVC) backing
- Flexible and conformable to awkward shapes
- Water resistant
- UV resistant
- Non-corrosive adhesive

TECHNICAL DATA

Colours:	Black, Red, Blue
Thickness:	0.18mm as per ASTM D1000
Length:	20 meter
Width:	18 mm
Flame Retardant:	UL57RJ pass
Breaking Load:	30 n/cm
Elongation:	240% as per AMST D1000
Adhesion to steel:	2.2 n/cm
Adhesion to it self:	2.0n/cm
Break down Voltage	6.0 kV
Service Temperature	-10°C to +80C
Storage Temperature	+12°C to +25°C

PRODUCT NUMBER	COLOUR	BARCODE	CASE SIZE	CARTON WEIGHT	QTY
61010	Black	0707273544889	20m X 18mm X 0.18mm	22.3 kg	250
61020	Red	0707273544902	20m X 18mm X 0.18mm	22.3 kg	250
61030	Blue	0707273544896	20m X 18mm X 0.18mm	22.3 kg	250
61040	Yellow	0707273544926	20m X 18mm X 0.18mm	22.3 kg	250
61050	Green	0606110159982	20m X 18mm X 0.18mm	22.3 kg	250
61060	White	0707273544919	20m X 18mm X 0.18mm	22.3 kg	250